DATASHEET

USB2.0 Connection Cable A-A, M-M, 1.0m, LSZH





General data

Supports data transmission rates up to 480 Mbit/s. Wire construction: AWG28 / AWG24. Shielded: Foil + 80% braiding. Plug moulded. Jacket: LSZH

Technical properties

Connection type connection 1	Plug
Connection type connection 2	Plug
Number of poles connection 1	4
Number of poles connection 2	4
Temperature	-10 – 60 °C
Type of connector connection 1	USB-A
Type of connector connection 2	USB-A

Available variants

ArtNr.	Bezeichnung	Colour	Length
K5204.1	USB2.0 Connection Cable A-A, M-M, 1.0m, LSZH	black	1.0 m

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de