

DATASHEET

USB3.0 Connection Cable A-A, M-M, 5.0m, black, Premium



General data

For data transmission rates up to 5 Gbit/s. Wire construction: AWG30 / AWG20. Shielding: Foil + 80% braiding. Plug moulded.

Technical properties

3D	False
ARC	False
Backwards compatible	True
Bandwith	5 Gbit/s
Bending radius (dynamic/static)	58 mm
CEC	False
Cable set	False
Chip	False
Compliant with	Communication equipment,Audio/video equipment,CT,MRI
Connection type connection 1	plug
Connection type connection 2	Stecker
Connector 1 angulation	180°
Connector 2 angulation	180°

This datasheet was created automatically on 25-09-2026 . Technical changes reserved.



DATASHEET

USB3.0 Connection Cable A-A, M-M, 5.0m, black, Premium

Contact Plating	gold-plated
Crush resistance (short/long)	1 kg/cm ²
DSC	False
Dust cover	No
HDMI Power	False
HDMI certified	False
HEC (Ethernet channel)	False
Halogenfree	No
Kink protection	False
MSA	False
MST	False
Material Connector Housing	PVC molded
Material Inner Conductor	TC
Material jacket	PVC
Max. mating cycles	1500
Model	Adapter
Number of poles connection 1	9
Number of poles connection 2	4
Number of shieldings	double
Operating temperature	-10 - 80 °C
PCIe Data transfer	False
Plug dimensions Side 1	28.1mm x 12mm x 4.5mm
Plug dimensions Side 2	28.1mm x 12mm x 4.5mm
Printing	USB3.0 SUPER SPEED PREMIUM CABLE AWM STYLE 2725 80°C 30V AWG30/AWG20
Scope of delivery	1 x USB Cable
Shielded	True
Speed	5 Gbit/s
Temperature	-10 - 80 °C
Tensile strength (short/long)	98,1 N
Type of connector connection 1	USB-A
Type of connector connection 2	USB-A
Type of packaging	plastic bag
Type of signal	Digital
VESA certified	False
VRR	False
Various lengths cable set	2 x 1m

This datasheet was created automatically on 25-09-2026 . Technical changes reserved.



DATASHEET

USB3.0 Connection Cable A-A, M-M, 5.0m, black, Premium

Version	USB 3.0 SuperSpeed
Warranty	24 months
With termination resistor	False
eARC	False

Available variants

ArtNr.	Bezeichnung	Colour	Length	Diameter	AWG
K5210SW.1	USB3.0 Connection Cable A-A, M-M, 1.0m, black, Premium	Black	1.0 m	5.8 mm	20+30AWG
K5210SW.1,8	USB3.0 Connection Cable A-A, M-M, 1.8m, black, Premium	Black	1.8 m	5.8 mm	20+30AWG
K5210SW.3	USB3.0 Connection Cable A-A, M-M, 3.0m, black, Premium	Black	3.0 m	5.8 mm	20+30AWG
K5210SW.5	USB3.0 Connection Cable A-A, M-M, 5.0m, black, Premium	Black	5.0 m	5.8 mm	20+30AWG

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 25-09-2026 . Technical changes reserved.

