

DATASHEET

USB2.0 Connection Cable A-Mini B (5pol), M-M, 5.0m, black, Premium



General data

For data transmission rates up to 480 Mbit/s. Wire diameter: AWG28 / AWG20. Shielding: Foil + 80% braiding. Plug moulded.

Technical properties

3D	False
ARC	False
Backwards compatible	True
CEC	False
Cable set	False
Chip	False
Connection type connection 1	Plug
Connection type connection 2	Plug
Contact Plating	gold-plated
DSC	False
Dust cover	false
HDMI Power	False
HDMI certified	False

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.



DATASHEET

USB2.0 Connection Cable A-Mini B (5pol), M-M, 5.0m, black, Premium

HEC (Ethernet channel)	False
Halogenfree	No
Kink protection	False
MSA	False
MST	False
Material Connector Housing	PVC molded
Model	Round Cable
Number of poles connection 1	4
Number of poles connection 2	5
Number of shieldings	double
PCIe Data transfer	False
Shielded	True
Temperature	-20 – 80 °C
Type of connector connection 1	USB-A
Type of connector connection 2	USB Mini-B
Type of packaging	plastic bag
VESA certified	False
VRR	False
Warranty	24 months
With termination resistor	False
eARC	False

Available variants

ArtNr.	Bezeichnung	Colour	Length	Diameter	AWG
K5251SW.1,8	USB2.0 Connection Cable A-Mini B (5pol), M-M, 1.8m, black, Premium	black	1.8 m	5.0 mm	20+28AWG
K5251SW.3	USB2.0 Connection Cable A-Mini B (5pol), M-M, 3.0m, black, Premium	black	3.0 m	5.0	20+28AWG
K5251SW.5	USB2.0 Connection Cable A-Mini B (5pol), M-M, 5.0m, black, Premium	black	5.0 m	5.0	20+28AWG

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

