

# DATASHEET

## USB2.0 Connection Cable A-B (angled), M-M, 1.8m, black, Classic



*Classic*



### General data

For data transmission rates up to 480 Mbit/s. Wire construction: AWG28 / AWG24. shielded: folie + braiding. Plug moulded.

### Technical properties

|                                 |                                                          |
|---------------------------------|----------------------------------------------------------|
| 3D                              | False                                                    |
| ARC                             | False                                                    |
| Backwards compatible            | True                                                     |
| Bandwith                        | 480 Mbit/s                                               |
| Bending radius (dynamic/static) | 45 mm                                                    |
| CEC                             | False                                                    |
| Cable set                       | False                                                    |
| Chip                            | False                                                    |
| Compliant with                  | Scanner, Printer, External hard drive, Medical equipment |
| Connection type connection 1    | Plug                                                     |
| Connection type connection 2    | Plug                                                     |
| Connector 1 angulation          | 180°                                                     |

This datasheet was created automatically on 20-09-2026 . Technical changes reserved.



# DATASHEET

## USB2.0 Connection Cable A-B (angled), M-M, 1.8m, black, Classic

|                                |                                                                        |
|--------------------------------|------------------------------------------------------------------------|
| Connector 2 angulation         | 90°                                                                    |
| Contact Plating                | gold-plated                                                            |
| Crush resistance (short/long)  | 1 kg/cm <sup>2</sup>                                                   |
| DSC                            | False                                                                  |
| Dust cover                     | false                                                                  |
| HDMI Power                     | False                                                                  |
| HDMI certified                 | False                                                                  |
| HEC (Ethernet channel)         | False                                                                  |
| Halogenfree                    | No                                                                     |
| Kink protection                | True                                                                   |
| MSA                            | False                                                                  |
| MST                            | False                                                                  |
| Material Connector Housing     | PVC molded                                                             |
| Material Inner Conductor       | TC                                                                     |
| Material jacket                | PVC                                                                    |
| Max. mating cycles             | 1500                                                                   |
| Model                          | Round Cable                                                            |
| Number of poles connection 1   | 4                                                                      |
| Number of poles connection 2   | 4                                                                      |
| Number of shieldings           | double                                                                 |
| Operating temperature          | -10 - 80 °C                                                            |
| PCIe Data transfer             | False                                                                  |
| Plug dimensions Side 1         | 36.7mm x 12mm x 4.5mm                                                  |
| Plug dimensions Side 2         | 21.5mm x 7.26mm x 8.65mm                                               |
| Printing                       | HI-SPEED USB Revision 2.0 SHIELDED<br>28AWG/1PR+24AWG/2C VW-1 80°C 30V |
| Scope of delivery              | 1 x USB Cable                                                          |
| Shielded                       | True                                                                   |
| Speed                          | 480 Mbit/s                                                             |
| Temperature                    | -10 - 80 °C                                                            |
| Tensile strength (short/long)  | 98,1 N                                                                 |
| Type of connector connection 1 | USB-A                                                                  |
| Type of connector connection 2 | USB-B                                                                  |
| Type of packaging              | plastic bag                                                            |
| Type of signal                 | Digital                                                                |
| VESA certified                 | False                                                                  |

This datasheet was created automatically on 20-09-2026 . Technical changes reserved.



# DATASHEET

## USB2.0 Connection Cable A-B (angled), M-M, 1.8m, black, Classic

|                           |                    |
|---------------------------|--------------------|
| VRR                       | False              |
| Version                   | USB 2.0 High-Speed |
| Warranty                  | 24 months          |
| With termination resistor | False              |
| eARC                      | False              |

### Available variants

| ArtNr.      | Bezeichnung                                                     | Colour | Length | Diameter | AWG      |
|-------------|-----------------------------------------------------------------|--------|--------|----------|----------|
| K5260SW.1,8 | USB2.0 Connection Cable A-B (angled), M-M, 1.8m, black, Classic | black  | 1.8 m  | 4.5 mm   | 24+28AWG |

### Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 20-09-2026 . Technical changes reserved.

