# DATASHEET

## USB2.0 Repeater Cable 5m active, USB-A Jack to USB-A Plug





| General data |
|---|
| USB2.0 Extension cable 5m, active 1-port hub with 5 m cable<br>USB-A receptacle to USB-A plug<br>Max. 4 x cascadable (= 25 m)<br>Integrated ASIC Chip as signal repeater/buffer<br>Power supply via USB-interface |

| Technical properties | |
|---|---|
| 3D | True |
| ARC | False |
| Backwards compatible | True |
| Bending radius (dynamic/static) | 40 mm |
| CEC | False |
| Cable set | False |
| Cable type (passive/active/optical) | passive |
| Chip | True |
| Color depth | 10-Bit |
| Connection type connection 1 | Plug |

**This datasheet was created automatically on 21-11-2026 . Technical changes reserved.**

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

# DATASHEET

## USB2.0 Repeater Cable 5m active, USB-A Jack to USB-A Plug

| | |
|---|---|
| Connection type connection 2 | jack |
| Connector 1 angulation | 180° |
| Connector 2 angulation | 180° |
| Contact Plating | silver-plated |
| DSC | False |
| Dust cover | false |
| Enhanced Color | Deep Color |
| HDMI Power | False |
| HDMI certified | False |
| HEC (Ethernet channel) | False |
| Halogenfree | No |
| Kink protection | True |
| MSA | False |
| MST | False |
| Material Connector Housing | PVC molded |
| Material Inner Conductor | BC |
| Material jacket | PVC |
| Max. mating cycles | 1500 |
| Model | Round Cable |
| Number of poles connection 1 | 5 |
| Number of poles connection 2 | 5 |
| Number of shieldings | triple |
| Operating temperature | -5 – 45 °C |
| PCIe Data transfer | False |
| Scope of delivery | 1xUSB Cable |
| Shielded | True |
| Supported audio formats | compressed Audio format (Dolby Digital, Dolby TrueHD, DTS, DTS-HD Master Audio, Dolby Atmos) |
| Supported video standards | HD - High Definition |
| Temperature | -20 – 70 °C |
| Tensile strength (short/long) | 98,1 N |
| Type of connector connection 1 | USB-A |
| Type of connector connection 2 | USB-A |
| Type of packaging | plastic bag |
| Type of signal | Digital |
| VESA certified | False |

**This datasheet was created automatically on 21-11-2026 . Technical changes reserved.**

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

# DATASHEET

## USB2.0 Repeater Cable 5m active, USB-A Jack to USB-A Plug

| | |
|---|---|
| VRR | False |
| Various lengths cable set | 1x5m |
| Version | USB 2.0 High-Speed |
| Warranty | 36 months |
| With termination resistor | False |
| eARC | False |

**Available variants**

| ArtNr. | Bezeichnung | Colour | Diameter | AWG |
|---|---|---|---|---|
| K5263.5V3 | USB2.0 Repeater Cable 5m active, USB-A Jack to USB-A Plug | black | 5.5 mm | 24AWG |

**Note on Intended Use**

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.



EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION