

DATASHEET

RJ45 Patch Cord Cat.6 S/FTP LSZH white 5m



General data

This Cat.6 LAN cable from EFB-Elektronik transmits data up to 5Gbit. S/FTP shielding reliably protects against interference and ensures good signal quality. Because it is a Cat.6 network cable, it offers a frequency range of up to 250MHz, which allows for high data transmission performance.

- Increase interference immunity in electromagnetically charged environments - double shielding (S/FTP) improves EMC reserve, reduces susceptibility to radiation and stabilizes transmission in parallel cable routing.
- Cover fire protection requirements in compliance with standards - flame-retardant cable behaviour according to IEC60332-1 reduces the spread of fire in the event of a fault and supports compliance with common installation specifications.
- Power and connect end devices via one cable - reduces cabling effort because data and power are transmitted via 4PPoE according to IEEE802.3bt on one line (fewer power supplies/sockets, faster installation).

Product Description

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.



DATASHEET

RJ45 Patch Cord Cat.6 S/FTP LSZH white 5m

The S/FTP LAN cable has a double shield that effectively reduces electromagnetic interference. The temperature range of the cable is -20 – 60 °C. The wide range of possible applications is supported by the bending radius of >31 mm. The Ethernet cable has an IP20 rating. The LSZH jacket is halogen-free and low-smoke. In the event of a fire, it minimizes smoke development and increases indoor safety.

Technical details

- Cat.6
- Connector: RJ45 8(8) to RJ45 8(8) with RJ45 connectors
- Shielding: S/FTP cable with 4x2 x AWG27/7
- Cable shape: round
- Pin assignment: 1:1 according to TIA/EIA 568B
- Equivalent to PoE class: PoE to IEEE802.3af, PoE+ to IEEE802.3at, and 4PPoE to IEEE802.3bt
- Gold-plated contacts
- Sheath: LSZH sheath material
- Outer diameter: 6.2 mm
- With an injected anti-kink grommet
- Fire protection: flame-retardant according to IEC60332-1, low-smoke according to IEC61034, halogen-free according to IEC60754-2
- Degree of protection: IP20
- With a punctual screen contact
- With locking lever protection
- Mating cycles: ≥750
- With length print
- Brand: EFB-Elektronik

Technical properties

AWG-size	27/7
Allocation	acc. TIA/EIA 568B
Anti-kink sleeve	moulded-on
Area of Application	Industrial Ethernet
Bandwidth	250MHz
Bending radius	>31 mm
Cable construction	4x2
Cable shape	rund
Cable type	S/FTP
Cabling standard	EN50173
Category	6
Colour anti-kink sleeve	white
Colour outer sheath	white
Conductive shield	Selected shield contact
Conductor Material	Copper
Conductor resistance DC	185 Ω/km

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.



DATASHEET

RJ45 Patch Cord Cat.6 S/FTP LSZH white 5m

Connector	IEC 60603-7-5
Connector type	RJ45 standard
Contact Resistance	30 mΩ
Contacts	Gold plated
Current capacity	max. 1 A
Fire retardant version	acc. IEC60332-1
Halogen free	acc. IEC60754-2
Harmonised Standard	EN 50575
Impedance	100
Insulation Resistance	10 MΩ
Length imprint	True
Locking lever	True
Loop resistance	370 Ω/km
Low smoke	acc. IEC61034
Material outer sheath	LSZH
Mating cycles	≥750
Model	shielded
Oil resistant	no
Operating Temperature	-20 - 60 °C
Operating-/ tempering voltage	max. 50 V DC
Outer diameter of the cable	6.2 mm
Ozone resistance	No
Pin assignment	1:1
Printing	SFTP 300 CAT.5E 26AWGX4P PATCH ISO/IEC 11801 & EN 50173 VERIFIED www.efb-elektronik.de
Resistance unbalance	5 %
Resistant to chemicals	False
Silicone-free	True
Suitable for degree of protection (IP)	IP20
Test voltage	1000 (V DC, 1min) core/core und core/screen
Transmission	5Gbit
Type of connector connection 1	RJ45 8(8)
Type of connector connection 2	RJ45 8(8)
UL approbated	False
UV resistant	Nein

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.



DATASHEET

RJ45 Patch Cord Cat.6 S/FTP LSZH white 5m

Available variants

ArtNr.	Bezeichnung	Length POE class		Length tolerance
K5518.0,15	RJ45 Patch Cord Cat.6 S/FTP LSZH white 0,15m	0.15 m	PoE acc. to IEEE802.3af;PoE acc. to IEEE802.3at;4PPoE acc. to IEEE802.3bt	±5 %
K5518.0,25	RJ45 Patch Cord Cat.6 S/FTP LSZH white 0,25m	0.25 m	PoE acc. to IEEE802.3af;PoE acc. to IEEE802.3at;4PPoE acc. to IEEE802.3bt	±5 %
K5518.0,5	RJ45 Patch Cord Cat.6 S/FTP LSZH white 0,5m	0.5 m	PoE acc. to IEEE802.3af;PoE acc. to IEEE802.3at;4PPoE acc. to IEEE802.3bt	±5 %
K5518.1	RJ45 Patch Cord Cat.6 S/FTP LSZH white 1m	1.0 m	PoE acc. to IEEE802.3af;PoE acc. to IEEE802.3at;4PPoE acc. to IEEE802.3bt	±5 %
K5518.1,5	RJ45 Patch Cord Cat.6 S/FTP LSZH white 1,5m	1.5 m	PoE acc. to IEEE802.3af;PoE acc. to IEEE802.3at;4PPoE acc. to IEEE802.3bt	±5 %
K5518.10	RJ45 Patch Cord Cat.6 S/FTP LSZH white 10m	10.0 m	PoE acc. to IEEE802.3af;PoE acc. to IEEE802.3at;4PPoE acc. to IEEE802.3bt	±5 %
K5518.15	RJ45 Patch Cord Cat.6 S/FTP LSZH white 15m	15.0 m	PoE acc. to IEEE802.3af;PoE acc. to IEEE802.3at	±5 %
K5518.2	RJ45 Patch Cord Cat.6 S/FTP LSZH white 2m	2.0 m	PoE acc. to IEEE802.3af;PoE acc. to IEEE802.3at;4PPoE acc. to IEEE802.3bt	±5 %
K5518.20	RJ45 Patch Cord Cat.6 S/FTP LSZH white 20m	20.0 m	PoE acc. to IEEE802.3af;PoE acc. to IEEE802.3at	±5 %
K5518.25	RJ45 Patch Cord Cat.6 S/FTP LSZH white 25m	25.0 m	PoE acc. to IEEE802.3af	±5 %
K5518.3	RJ45 Patch Cord Cat.6 S/FTP LSZH white 3m	3.0 m	PoE acc. to IEEE802.3af;PoE acc. to IEEE802.3at;4PPoE acc. to IEEE802.3bt	±5 %
K5518.30	RJ45 Patch Cord Cat.6 S/FTP LSZH white 30m	30.0 m	PoE acc. to IEEE802.3af	±5 %
K5518.40	RJ45 Patch Cord Cat.6 S/FTP LSZH white 40m	40.0 m	No	±5 %
K5518.5	RJ45 Patch Cord Cat.6 S/FTP LSZH white 5m	5.0 m	PoE acc. to IEEE802.3af;PoE acc. to IEEE802.3at;4PPoE acc. to IEEE802.3bt	±5 %
K5518.50	RJ45 Patch Cord Cat.6 S/FTP LSZH white 50m	50.0 m	No	±5 %
K5518.7,5	RJ45 Patch Cord Cat.6 S/FTP LSZH white 7,5m	7.5 m	PoE acc. to IEEE802.3af;PoE acc. to IEEE802.3at;4PPoE acc. to IEEE802.3bt	±5 %

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

