
# DATASHEET

## RJ45 Patch Cord Cat.6A S/FTP TPE Cat.7 raw cable superflex yellow 0,25m




### General data

The Cat.6A (IEC) LAN cable from EFB-Elektronik supports 10Gbit. The S/FTP shielding reliably protects against interference and ensures high-quality signal. Since it is a Cat.6A (IEC) network cable, it offers a frequency range of up to 500MHz, which provides high data transmission performance.

• Increase interference immunity in electromagnetically charged environments – double shielding (S/FTP) improves EMC reserve, reduces susceptibility to radiation and stabilizes transmission in parallel cable routing.
• Cover fire protection requirements in compliance with standards – flame-retardant cable behaviour according to IEC60332-1 reduces the spread of fire in the event of a fault and supports compliance with common installation specifications.
• Power and connect devices via a cable – reduces cabling effort because data and power are transmitted via 4PPoE to IEEE802.3bt on a single line. 4PPoE according to IEEE802.3bt can only be used up to certain cable lengths.

**This datasheet was created automatically on 01-11-2026 . Technical changes reserved.**

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

# DATASHEET

## RJ45 Patch Cord Cat.6A S/FTP TPE Cat.7 raw cable superflex yellow 0,25m

Product Description
The S/FTP LAN cable has a double shield that effectively reduces electromagnetic interference. It can be used in a temperature range of -20 – 60 °C. The wide range of possible applications is supported by the bending radius of >32.5 mm. The patch cable has an IP20 rating. The TPE/LSZH jacket is flexible, halogen-free and low-smoke, making it ideal for safe and professional patch and server cabinet installations.

Technical details
• Cat.6A (IEC)
• Connector: RJ45 8(8) to RJ45 8(8) with blue RJ45 connectors
• Shielding: S/FTP cable with 4x2 x AWG26/7
• Cable shape: round
• Pin assignment: 1:1 according to TIA/EIA 568B
• Equivalent to PoE class: PoE to IEEE802.3af, PoE+ to IEEE802.3at, and 4PPoE to IEEE802.3bt
• Gold-plated contacts
• Sheath: TPE/LSZH sheath material
• Outer diameter: 6.5 mm
• With an injected anti-kink grommet
• Fire protection: flame-retardant according to IEC60332-1, low-smoke according to IEC61034, halogen-free according to IEC60754-2
• Degree of protection: IP20
• With a 360° umbrella attachment
• With locking lever protection
• Mating cycles: ≥750
• With length print
• Brand: EFB-Elektronik

| **Technical properties** | |
|---|---|
| AWG-size | 26/7 |
| Allocation | acc. TIA/EIA 568B |
| Anti-kink sleeve | moulded-on |
| Area of Application | Industrial Ethernet |
| Bandwidth | 500MHz |
| Bending radius | >32,5 mm |
| Cable construction | 4x2 |
| Cable shape | rund |
| Cable type | S/FTP |
| Cabling standard | EN50173 |
| Category | 6A (IEC) |
| Colour anti-kink sleeve | yellow |
| Colour outer sheath | yellow |
| Conductive shield | 360° shield contact |

# DATASHEET

## RJ45 Patch Cord Cat.6A S/FTP TPE Cat.7 raw cable superflex yellow 0,25m

| | |
|---|---|
| Conductor Material | Copper |
| Conductor resistance DC | 142 Ω/km |
| Connector | IEC 60603-7-51 |
| Connector type | RJ45 standard blue |
| Contact Resistance | 30 mΩ |
| Contacts | Gold plated |
| Current capacity | max. 1 A |
| Fire retardant version | acc. IEC60332-1 |
| Halogen free | acc. IEC60754-2 |
| Harmonised Standard | EN 50575 |
| Impedance | 100 ±25 Ω |
| Insulation Resistance | 100 MΩ |
| Length imprint | True |
| Locking lever | True |
| Loop resistance | 284 Ω/km |
| Low smoke | acc. IEC61034 |
| Material outer sheath | TPE/LSZH |
| Mating cycles | ≥750 |
| Model | shielded |
| Oil resistant | no |
| Operating Temperature | -20 – 60 °C |
| Operating-/ tempering voltage | max. 50 V DC |
| Outer diameter of the cable | 6.5 mm |
| Ozone resistance | No |
| Pin assignment | 1:1 |
| Printing | SFTP 300 CAT.5E 26AWGX4P PATCH ISO/IEC 11801 & EN 50173 VERIFIED www.efb-elektronik.de |
| Raw cable | Cat.7 |
| Resistance unbalance | 2 % |
| Resistant to chemicals | False |
| Silicone-free | True |
| Suitable for degree of protection (IP) | IP20 |
| Test voltage | 1000 (V DC, 1min) core/core und core/screen |
| Transmission | 10Gbit |
| Type of connector connection 1 | RJ45 8(8) |
| Type of connector connection 2 | RJ45 8(8) |

**This datasheet was created automatically on 01-11-2026 . Technical changes reserved.**

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

# DATASHEET

## RJ45 Patch Cord Cat.6A S/FTP TPE Cat.7 raw cable superflex yellow 0,25m

| | |
|---|---|
| UL approbated | False |
| UV resistant | Nein |

**Available variants**

| ArtNr. | Bezeichnung | Length | POE class | Length tolerance |
|---|---|---|---|---|
| K5525FGE.0,15 | RJ45 Patch Cord Cat.6A S/FTP TPE Cat.7 raw cable superflex yellow 0,15m | 0.15 m | PoE acc. to IEEE802.3af;PoE+ acc. to IEEE802.3at;4PPoE acc. to IEEE802.3bt | ±5 % |
| K5525FGE.0,25 | RJ45 Patch Cord Cat.6A S/FTP TPE Cat.7 raw cable superflex yellow 0,25m | 0.25 m | PoE acc. to IEEE802.3af;PoE+ acc. to IEEE802.3at;4PPoE acc. to IEEE802.3bt | ±5 % |
| K5525FGE.0,5 | RJ45 Patch Cord Cat.6A S/FTP TPE Cat.7 raw cable superflex yellow 0,5m | 0.5 m | PoE acc. to IEEE802.3af;PoE+ acc. to IEEE802.3at;4PPoE acc. to IEEE802.3bt | ±5 % |
| K5525FGE.1 | RJ45 Patch Cord Cat.6A S/FTP TPE Cat.7 raw cable superflex yellow 1m | 1.0 m | PoE acc. to IEEE802.3af;PoE+ acc. to IEEE802.3at;4PPoE acc. to IEEE802.3bt | ±5 % |
| K5525FGE.1,5 | RJ45 Patch Cord Cat.6A S/FTP TPE Cat.7 raw cable superflex yellow 1,5m | 1.5 m | PoE acc. to IEEE802.3af;PoE+ acc. to IEEE802.3at;4PPoE acc. to IEEE802.3bt | ±5 % |
| K5525FGE.10 | RJ45 Patch Cord Cat.6A S/FTP TPE Cat.7 raw cable superflex yellow 10m | 10.0 m | PoE acc. to IEEE802.3af;PoE+ acc. to IEEE802.3at;4PPoE acc. to IEEE802.3bt | ±5 % |
| K5525FGE.15 | RJ45 Patch Cord Cat.6A S/FTP TPE Cat.7 raw cable superflex yellow 15m | 15.0 m | PoE acc. to IEEE802.3af;PoE+ acc. to IEEE802.3at;4PPoE acc. to IEEE802.3bt | ±5 % |
| K5525FGE.2 | RJ45 Patch Cord Cat.6A S/FTP TPE Cat.7 raw cable superflex yellow 2m | 2.0 m | PoE acc. to IEEE802.3af;PoE+ acc. to IEEE802.3at;4PPoE acc. to IEEE802.3bt | ±5 % |
| K5525FGE.20 | RJ45 Patch Cord Cat.6A S/FTP TPE Cat.7 raw cable superflex yellow 20m | 20.0 m | PoE acc. to IEEE802.3af;PoE+ acc. to IEEE802.3at;4PPoE acc. to IEEE802.3bt | ±5 % |
| K5525FGE.25 | RJ45 Patch Cord Cat.6A S/FTP TPE Cat.7 raw cable superflex yellow 25m | 25.0 m | PoE acc. to IEEE802.3af;PoE+ acc. to IEEE802.3at | ±5 % |
| K5525FGE.3 | RJ45 Patch Cord Cat.6A S/FTP TPE Cat.7 raw cable superflex yellow 3m | 3.0 m | PoE acc. to IEEE802.3af;PoE+ acc. to IEEE802.3at;4PPoE acc. to IEEE802.3bt | ±5 % |
| K5525FGE.30 | RJ45 Patch Cord Cat.6A S/FTP TPE Cat.7 raw cable superflex yellow 30m | 30.0 m | PoE acc. to IEEE802.3af;PoE+ acc. to IEEE802.3at | ±5 % |
| K5525FGE.5 | RJ45 Patch Cord Cat.6A S/FTP TPE Cat.7 raw cable superflex yellow 5m | 5.0 m | PoE acc. to IEEE802.3af;PoE+ acc. to IEEE802.3at;4PPoE acc. to IEEE802.3bt | ±5 % |
| K5525FGE.7,5 | RJ45 Patch Cord Cat.6A S/FTP TPE Cat.7 raw cable superflex yellow 7,5m | 7.5 m | PoE acc. to IEEE802.3af;PoE+ acc. to IEEE802.3at;4PPoE acc. to IEEE802.3bt | ±5 % |

**Note on Intended Use**

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a



EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

**This datasheet was created automatically on 01-11-2026 . Technical changes reserved.**

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION