

DATASHEET

RJ45 Patch Cord Cat.6A S/FTP TPE superflex grey 1m



Cat.6A	10 Gbit
500 MHz	100% CU
GHMT	ETL

General data

This Cat.6A (TIA) patch cable from EFB-Elektronik transmits data up to 10Gbit. The S/FTP shielding reliably protects against interference and ensures good signal quality. Since it is a Cat.6A (TIA) patch cable, it supports a frequency range of up to 500MHz, which enables high data transmission performance.

- Increase interference immunity in electromagnetically charged environments – double shielding (S/FTP) improves EMC reserve, reduces susceptibility to radiation and stabilizes transmission in parallel cable routing.
- Cover fire protection requirements in compliance with standards – flame-retardant cable behaviour according to IEC60332-1 reduces the spread of fire in the event of a fault and supports compliance with common installation specifications.
- Better visibility and safer evacuation in the event of an emergency after IEC61034 – low smoke development helps to keep escape routes as low-smoke as possible in the event of a fire.

Product Description

The S/FTP network cable has double shielding, which effectively reduces electromagnetic interference. The temperature range of the cable is -20 – 60 °C. The wide range of possible applications is supported by the bending radius of 5 x D. The LSZH jacket is halogen-free and low-smoke. In the event of a fire, it minimizes smoke development and increases indoor safety. It is also oil-resistant.

Technical details

- Cat.6A (TIA)

This datasheet was created automatically on 11-09-2026 . Technical changes reserved.



DATASHEET

RJ45 Patch Cord Cat.6A S/FTP TPE superflex grey 1m

- Connector: RJ45 8(8) to RJ45 8(8) with RJ45 connectors
- Shielding: S/FTP cable with 4x2 x AWG26/7
- Pinout: 1:1
- Equivalent to PoE class: PoE to IEEE802.3af, PoE+ to IEEE802.3at, and 4PPoE to IEEE802.3bt
- Sheath: LSZH sheath material
- Oil-resistant according to EN 60811-404
- Outer diameter: 6.0 mm
- With an injected anti-kink grommet
- Fire protection: flame-retardant according to IEC60332-1, low-smoke according to IEC61034
- With locking lever protection
- Brand: EFB-Elektronik

Technical properties	
AWG-size	26/7
Anti-kink sleeve	moulded-on
Area of Application	Industrial Ethernet
Bandwidth	500MHz
Bending radius	5 x D
Cable construction	4x2
Cable type	S/FTP
Cabling standard	ANSI/TIA-568-C.2
Category	6A (TIA)
Colour anti-kink sleeve	blue
Colour outer sheath	blue
Conductor Material	Copper
Fire retardant version	acc. IEC60332-1
Locking lever	True
Low smoke	acc. IEC61034
Material outer sheath	LSZH
Model	shielded
Oil resistant	acc. EN 60811-404
Operating Temperature	-20 - 60 °C
Outer diameter of the cable	6.0 mm
Pin assignment	1:1
Printing	Cat.6 S/FTP 4x2xAWG27/7 PIMF ISO/IEC 11801 & EN50173-1 TIA/EIA 568B.2-1 Halogen Free ***Gigabit*** www.efb-elektronik.de
Raw cable	Cat.7
Transmission	10Gbit
Type of connector connection 1	RJ45 8(8)

This datasheet was created automatically on 11-09-2026 . Technical changes reserved.



DATASHEET

RJ45 Patch Cord Cat.6A S/FTP TPE superflex grey 1m

Type of connector connection 2

RJ45 8(8)

Available variants

ArtNr.	Bezeichnung	Length	POE class
K5534FBL.5	RJ45 Patch cable S/FTP, Cat.6A, TPE superflex, 5m, blue	5.0 m	PoE nach IEEE802.3af;PoE+ nach IEEE802.3at;4PPoE nach IEEE802.3bt
K5534FGE.1	RJ45 Patch cable S/FTP, Cat.6A, TPE superflex, 1m, yellow	1.0 m	keine
K5534FGN.10	RJ45 Patch Cord Cat.6A S/FTP TPE superflex green 10m	10.0 m	PoE nach IEEE802.3af;PoE+ nach IEEE802.3at;4PPoE nach IEEE802.3bt
K5534FGR.1	RJ45 Patch Cord Cat.6A S/FTP TPE superflex grey 1m	1.0 m	PoE nach IEEE802.3af;PoE+ nach IEEE802.3at;4PPoE nach IEEE802.3bt
K5534FRT.10	RJ45 Patch Cord Cat.6A S/FTP TPE superflex red 10m	10.0 m	keine
K5534FRT.3	RJ45 Patch Cord Cat.6A S/FTP TPE superflex red 3m	3.0 m	PoE nach IEEE802.3af;PoE+ nach IEEE802.3at;4PPoE nach IEEE802.3bt
K5534FRT.7,5	RJ45 Patch Cord Cat.6A S/FTP TPE superflex red 7,5m	7.5 m	keine

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 11-09-2026 . Technical changes reserved.

