


DATASHEET

RJ45 Patch Cord Cat.6A S/FTP PVC UL grey 30m



General data

The Cat.6A (TIA) data cable from the EFB-Elektronik brand supports data transmissions up to 10Gbit. The S/FTP shielding reliably protects against interference and ensures high signal quality. Because it is a Cat.6A (TIA) data cable, it offers a frequency range of up to 500MHz, which provides high data transmission performance.

- Increase interference immunity in electromagnetically charged environments – double shielding (S/FTP) improves EMC reserve, reduces susceptibility to radiation and stabilizes transmission in parallel cable routing.
- Cover fire protection requirements in compliance with standards – flame-retardant cable behaviour according to IEC60332-1 reduces the spread of fire in the event of a fault and supports compliance with common installation specifications.
- Reliable performance for your network connection – the pure copper conductor material ensures stable data transmission and supports consistent signal quality in typical IT and home network applications.

Product Description

The S/FTP patch cable has a double shield that effectively reduces electromagnetic interference. The temperature range of the cable is -20 – 75 °C. The wide range of possible applications is supported by the bending radius of >34 mm. The patch cord is IP20 rated. The polyvinyl chloride (PVC) jacket is a flexible standard jacket for network applications, without special fire protection properties.

Technical details

- Cat.6A (TIA)

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.



DATASHEET

RJ45 Patch Cord Cat.6A S/FTP PVC UL grey 30m

- Connector: RJ45 8(8) to RJ45 8(8) with RJ45 connectors
- Shielding: S/FTP cable with 4x2 x AWG24/7
- Cable shape: round
- Pin assignment: 1:1 according to TIA/EIA 568B
- Equivalent to PoE class: PoE to IEEE802.3af, PoE+ to IEEE802.3at, and 4PPoE to IEEE802.3bt
- UL approved
- Gold-plated contacts
- Sheath: Polyvinyl chloride (PVC) sheath material
- Outer diameter: 6.8 mm
- With an injected anti-kink grommet
- Fire protection: flame-retardant according to IEC60332-1
- Degree of protection: IP20
- With a 360° umbrella attachment
- With locking lever protection
- Mating cycles: ≥ 750
- Brand: EFB-Elektronik

Technical properties

AWG-size	24/7
Allocation	acc. TIA/EIA 568B
Anti-kink sleeve	moulded-on
Area of Application	Industrial Ethernet
Bandwidth	500MHz
Bending radius	>34 mm
Cable construction	4x2
Cable shape	rund
Cable type	S/FTP
Cabling standard	EN50173
Category	6A (TIA)
Colour anti-kink sleeve	grey
Colour outer sheath	grey
Conductive shield	360° shield contact
Conductor Material	Copper
Connector	IEC 60603-7-51
Connector type	RJ45 standard
Contact Resistance	< 20 mΩ
Contacts	Gold plated
Current capacity	max. 1 A
Fire retardant version	acc. IEC60332-1
Halogen free	False
Harmonised Standard	EN 50575

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.



DATASHEET

RJ45 Patch Cord Cat.6A S/FTP PVC UL grey 30m

Impedance	100 $\pm$ 15 Ω
Insulation Resistance	500 M Ω
Length imprint	False
Locking lever	True
Material outer sheath	Polyvinylchlorid (PVC)
Mating cycles	$\geq$ 750
Model	shielded
Oil resistant	no
Operating Temperature	-20 - 75 $^{\circ}$ C
Operating-/ tempering voltage	max. 50 V DC
Outer diameter of the cable	6.8 mm
Ozone resistance	No
Pin assignment	1:1
Printing	E132276-C (UL) CM 75 $^{\circ}$ 4PR 26AWG CSA LL64151-C CMG 75 $^{\circ}$ C FT4 Cat.6(A) SSTP PATCH CORD
Resistant to chemicals	False
Suitable for degree of protection (IP)	IP20
Test voltage	1000 (V DC, 1min) core/core und core/screen
Transmission	10Gbit
Type of connector connection 1	RJ45 8(8)
Type of connector connection 2	RJ45 8(8)
UL approbated	True
UV resistant	Nein

Available variants

ArtNr.	Bezeichnung	Length POE class		Length tolerance
K5537GR.20	RJ45 Patch Cord Cat.6A S/FTP PVC UL grey 20m	20.0 m	PoE acc. to IEEE802.3af;PoE+ acc. to IEEE802.3at;4PPoE acc. to IEEE802.3bt	$\pm$ 5 %
K5537GR.30	RJ45 Patch Cord Cat.6A S/FTP PVC UL grey 30m	30.0 m	PoE acc. to IEEE802.3af;PoE+ acc. to IEEE802.3at;4PPoE acc. to IEEE802.3bt	$\pm$ 5 %
K5537GR.40	RJ45 Patch Cord Cat.6A S/FTP PVC UL grey 40m	40.0 m	PoE acc. to IEEE802.3af;PoE+ acc. to IEEE802.3at;4PPoE acc. to IEEE802.3bt	$\pm$ 5 %
K5537GR.50	RJ45 Patch Cord Cat.6A S/FTP PVC UL grey 50m	50.0 m	PoE acc. to IEEE802.3af;PoE+ acc. to IEEE802.3at;4PPoE acc. to IEEE802.3bt	$\pm$ 5 %
K5537GR.60	RJ45 Patch Cord Cat.6A S/FTP PVC UL grey 60m	60.0 m	PoE acc. to IEEE802.3af;PoE+ acc. to IEEE802.3at;4PPoE acc. to IEEE802.3bt	$\pm$ 5 %
K5537GR.70	RJ45 Patch Cord Cat.6A S/FTP PVC UL grey 70m	70.0 m	PoE acc. to IEEE802.3af;PoE+ acc. to IEEE802.3at;4PPoE acc. to IEEE802.3bt	$\pm$ 5 %

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.



DATASHEET

RJ45 Patch Cord Cat.6A S/FTP PVC UL grey 30m

K5537GR.80	RJ45 Patch Cord Cat.6A S/FTP PVC UL grey 80m	80.0 m	PoE acc. to IEEE802.3af;PoE+ acc. to IEEE802.3at;4PPoE acc. to IEEE802.3bt	±5 %
K5537GR.90	RJ45 Patch Cord Cat.6A S/FTP PVC UL grey 90m	90.0 m	PoE acc. to IEEE802.3af;PoE+ acc. to IEEE802.3at;4PPoE acc. to IEEE802.3bt	±5 %

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

