DATASHEET

RJ45 Flat Patch Cord Cat.6A U/FTP PVC white 3m



General data

The Cat.6A (TIA) LAN cable from EFB-Elektronik transmits data up to 10Gbit. The U/FTP shielding reliably protects against interference and ensures high-quality signals. Because it is a Cat.6A (TIA) Ethernet cable, it offers a frequency range of up to 500MHz, which provides high data transmission performance.

• Space-saving cabling – the flat cable enables kink-free installation in confined spaces.
• Cover fire protection requirements in compliance with standards – flame-retardant cable behaviour according to IEC60332-1 reduces the spread of fire in the event of a fault and supports compliance with common installation specifications.
• Supply and connect end devices via one cable – reduces cabling effort because data and power are transmitted via PoE+ according to IEEE802.3at on a single line. PoE+ according to IEEE802.3at can only be used up to certain cable lengths.

Product Description

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

DATASHEET

RJ45 Flat Patch Cord Cat.6A U/FTP PVC white 3m

This data cable offers improved interference resistance at the pair level (U/FTP) – individually foil-shielded wire pairs reduce crosstalk, increase data security, and ensure stable high-speed transmission. It can be used in a temperature range of -20 – 60 °C. The wide range of possible applications is supported by the bending radius of >20 mm. The Ethernet cable has an IP20 rating. The polyvinyl chloride (PVC) jacket is a flexible standard jacket for network applications, without special fire protection properties.

Technical details
- Cat.6A (TIA)
- Connector: RJ45 8(8) to RJ45 8(8) with extra-short RJ45 connectors
- Shielding: U/FTP cable with 4x2 x AWG30/7
- Cable shape: flat
- Pin assignment: 1:1 according to TIA/EIA 568B
- Corresponds to PoE class: PoE according to IEEE802.3af and PoE+ according to IEEE802.3at
- Gold-plated contacts
- Sheath: Polyvinyl chloride (PVC) sheath material
- External dimensions of the cable: 7.0*2.2 mm
- With an injected anti-kink grommet
- Fire protection: flame-retardant according to IEC60332-1
- Degree of protection: IP20
- With a punctual screen contact
- With locking lever protection
- Mating cycles: ≥750
- Brand: EFB-Elektronik

Technical properties	
AWG-size	30/7
Allocation	acc. TIA/EIA 568B
Anti-kink sleeve	moulded-on
Area of Application	Industrial Ethernet
Bandwidth	500MHz
Bending radius	>20 mm
Cable construction	4x2
Cable shape	flat
Cable type	U/FTP
Cabling standard	EN50173
Category	6A (TIA)
Colour anti-kink sleeve	white
Colour outer sheath	white
Conductive shield	Selected shield contact
Conductor Material	Copper
Conductor resistance DC	376 Ω/km
Connector	IEC 60603-7-51

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

DATASHEET

RJ45 Flat Patch Cord Cat.6A U/FTP PVC white 3m

Connector type	RJ45 short version
Contacts	Gold plated
Current capacity	max. 1 A
Fire retardant version	acc. IEC60332-1
Halogen free	False
Harmonised Standard	EN 50575
Impedance	100 ±15 Ω
Insulation Resistance	100 MΩ
Length imprint	False
Locking lever	True
Loop resistance	752 Ω/km
Material outer sheath	Polyvinylchlorid (PVC)
Mating cycles	≥750
Model	shielded
NVP value	76 %
Oil resistant	no
Operating Temperature	-20 – 60 °C
Operating-/ tempering voltage	max. 50 V DC
Outer diameter of the cable	7.0*2.2 mm
Ozone resistance	No
Pin assignment	1:1
Printing	SLIM PATCHCABLE U/FTP CAT.6A ***10GE***
Resistance unbalance	< 4 %
Resistant to chemicals	False
Silicone-free	True
Suitable for degree of protection (IP)	IP20
Test voltage	1000 (V DC, 1min) core/core und core/screen
Transmission	10Gbit
Type of connector connection 1	RJ45 8(8)
Type of connector connection 2	RJ45 8(8)
UL approbated	False
UV resistant	Nein

Available variants

ArtNr.	Bezeichnung	Length	POE class	Length tolerance

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

DATASHEET

RJ45 Flat Patch Cord Cat.6A U/FTP PVC white 3m

K5545WS.0,15	RJ45 Flat Patch Cord Cat.6A U/FTP PVC white 0.15m	0.15 m	PoE acc. to IEEE802.3af;PoE acc. to IEEE802.3at	±5 %
K5545WS.0,25	RJ45 Flat Patch Cord Cat.6A U/FTP PVC white 0,25m	0.25 m	PoE acc. to IEEE802.3af;PoE acc. to IEEE802.3at	±5 %
K5545WS.0,5	RJ45 Flat Patch Cord Cat.6A U/FTP PVC white 0,5m	0.5 m	PoE acc. to IEEE802.3af;PoE acc. to IEEE802.3at	±5 %
K5545WS.1	RJ45 Flat Patch Cord Cat.6A U/FTP PVC white 1m	1.0 m	PoE acc. to IEEE802.3af;PoE acc. to IEEE802.3at	±5 %
K5545WS.1,5	RJ45 Flat Patch Cord Cat.6A U/FTP PVC white 1,5m	1.5 m	PoE acc. to IEEE802.3af	±5 %
K5545WS.2	RJ45 Flat Patch Cord Cat.6A U/FTP PVC white 2m	2.0 m	PoE acc. to IEEE802.3af	±5 %
K5545WS.3	RJ45 Flat Patch Cord Cat.6A U/FTP PVC white 3m	3.0 m	PoE acc. to IEEE802.3af	±5 %
K5545WS.5	RJ45 Flat Patch Cord Cat.6A U/FTP PVC white 5m	5.0 m	PoE acc. to IEEE802.3af	±5 %

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION