

DATASHEET

DisplayPort 1.2 Cable 4K 60Hz,A-A M-M, Premium ZDC housing, 2m, black



General data

According to DisplayPort1.4 standard

Resolution up to 4K Ultra HD (4096 x 2160 @ 60Hz)

Premium Zinc-die-cast housing with full EMC shielding and DP lock

DisplayPort plugs and contacts gold plated

Tripple shielding

Conductor: bare copper, Jacket: PVC

Pin 20: DP_PWR not connected

Technical properties

3D	True
ARC	True
Backwards compatible	True
Bending radius (dynamic/static)	40 mm
CEC	False
Cable set	False
Cable type (passive/active/optical)	passive
Chip	False
Color depth	12-Bit

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.



DATASHEET

DisplayPort 1.2 Cable 4K 60Hz,A-A M-M, Premium ZDC housing, 2m, black

Compressions technologies	DSC
Connection type connection 1	Plug
Connection type connection 2	Plug
Connector 1 angulation	180°
Connector 2 angulation	180°
Contact Plating	gold-plated
DSC	True
Dust cover	True
HDCP Version	HDCP 1.3
HDMI Power	False
HDMI certified	False
HDR	HDR
HEC (Ethernet channel)	False
Halogenfree	No
Kink protection	True
MSA	False
MST	False
Material Connector Housing	PVC molded
Material Inner Conductor	BC
Material jacket	PVC
Max. mating cycles	5000
Max. resolution	4K@60Hz
Model	Round Cable
Number of poles connection 1	20
Number of poles connection 2	19
Number of shieldings	triple
Operating temperature	-5 - 45 °C
PCIe Data transfer	False
Plug dimensions Side 1	21*11*44mm
Plug dimensions Side 2	21*11*44mm
Printing	Displayport Cable AWM STYLE 20276 80°C 30V VW-1
Scope of delivery	1xDP Cable
Shielded	True
Speed	25,92 Gbit/s
Supported audio formats	compressed Audio format (Dolby Digital, Dolby TrueHD, DTS, DTS-HD Master Audio, Dolby Atmos)

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.



DATASHEET

DisplayPort 1.2 Cable 4K 60Hz,A-A M-M, Premium ZDC housing, 2m, black

Supported video standards	4K UHD - Ultra High Definition
Temperature	-20 – 70 °C
Tensile strength (short/long)	98,1 N
Type of connector connection 1	DisplayPort (DP)
Type of connector connection 2	DisplayPort (DP)
Type of locking	Snap-in Locking
Type of packaging	plastic bag
Type of signal	Digital
VESA certified	False
VRR	False
Various lengths cable set	1x1m
Version	HDMI Version 1.2
Warranty	36 months
With termination resistor	False
eARC	False

Available variants

ArtNr.	Bezeichnung	Colour	Length	Diameter	AWG
K5560HQS.W.1	DisplayPort 1.2 Cable 4K 60Hz,A-A M-M, Premium ZDC housing, 1m, black	black	1.0 m	7.3 mm	30AWG
K5560HQS.W.10	DisplayPort 1.2 Cable 4K 60Hz,A-A M-M, Premium ZDC housing, 10m, black	black	10.0 m	7.3 mm	28AWG
K5560HQS.W.2	DisplayPort 1.2 Cable 4K 60Hz,A-A M-M, Premium ZDC housing, 2m, black	black	2.0 m	7.3 mm	30AWG
K5560HQS.W.3	DisplayPort 1.2 Cable 4K 60Hz,A-A M-M, Premium ZDC housing, 3m, black	black	3.0 m	7.3 mm	30AWG
K5560HQS.W.5	DisplayPort 1.2 Cable 4K 60Hz,A-A M-M, Premium ZDC housing, 5m, black	black	5.0 m	7.3 mm	30AWG

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

