

DATASHEET

DisplayPort/HDMI Cable 4K60Hz,A-A M-M, 1m, black



General data

DisplayPort to HDMI Adapter cable with one sided signal way DisplayPort => HDMI output device
 Supports 4K @ 60Hz resolution
 Shielding: foil + braiding
 Conductor: bare copper, Jacket: PVC
 Plugs and contacts gold plated, HDMI side moulded, DP mounted with locking protection
 Pin 20: DP_PWR not connected

Technical properties

3D	True
ARC	True
Backwards compatible	True
Bending radius (dynamic/static)	40 mm
CEC	True
Cable and plug compatibility	High-Speed HDMI
Cable set	False
Cable type (passive/active/optical)	passive
Chip	True
Color depth	12-Bit

This datasheet was created automatically on 24-09-2026 . Technical changes reserved.



DATASHEET

DisplayPort/HDMI Cable 4K60Hz,A-A M-M, 1m, black

Compliant with	TV
Compressions technologies	DSC
Connection type connection 1	Stecker
Connection type connection 2	Stecker
Connector 1 angulation	180°
Connector 2 angulation	180°
Contact Plating	gold-plated
DSC	True
Dust cover	True
Enhanced Color	Deep Color
HDMI Power	True
HDMI certified	True
HDR	HDR
HEC (Ethernet channel)	True
Halogenfree	No
Kink protection	True
MSA	False
MST	False
Material Connector Housing	PVC molded
Material Inner Conductor	BC
Material jacket	PVC
Max. mating cycles	5000
Max. resolution	4K@60Hz
Model	Adapter
Number of poles connection 1	20
Number of poles connection 2	20
Number of shieldings	triple
Operating temperature	-5 - 45 °C
PCIe Data transfer	False
Plug dimensions Side 1	20*12*51mm
Plug dimensions Side 2	19.3*9.9*37.3mm
Printing	Displayport Cable AWM STYLE 20276 80°C 30V VW-1 www.efb-elektronik.de
Scope of delivery	1xDP-HDMI Cable
Shielded	True
Speed	25,92 Gbit/s

This datasheet was created automatically on 24-09-2026 . Technical changes reserved.



DATASHEET

DisplayPort/HDMI Cable 4K60Hz,A-A M-M, 1m, black

Supported audio formats	compressed Audio format (Dolby Digital, Dolby TrueHD, DTS, DTS-HD Master Audio, Dolby Atmos)
Supported video standards	4K UHD - Ultra High Definition
Temperature	-20 - 70 °C
Tensile strength (short/long)	98,1 N
Type of connector connection 1	DisplayPort (DP)
Type of connector connection 2	HDMI Type A
Type of locking	Snap-in Locking
Type of packaging	plastic bag
Type of signal	Digital
VESA certified	False
VRR	False
Various lengths cable set	1x1m
Version	HDMI Version 2.0
Warranty	36 months
With termination resistor	False
eARC	False

Available variants

ArtNr.	Bezeichnung	Colour	Length	Diameter	AWG
K5561HQS.W.1	DisplayPort/HDMI Cable 4K60Hz,A-A M-M, 1m, black	Black	1.0 m	7.3 mm	30AWG
K5561HQS.W.2	DisplayPort/HDMI Cable 4K60Hz,A-A M-M, 2m, black	Black	2.0 m	7.3 mm	30AWG
K5561HQS.W.3	DisplayPort/HDMI Cable 4K60Hz,A-A M-M, 3m, black	Black	3.0 m	7.3 mm	30AWG
K5561HQS.W.5	DisplayPort/HDMI Cable 4K60Hz,A-A M-M, 5m, black	Black	5.0 m	7.3 mm	30AWG

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 24-09-2026 . Technical changes reserved.

