

DATASHEET

Mini DisplayPort – DisplayPort Cable, M-M, 3m, black



General data

Shielding: foil + braiding
 Conductor: bare copper, Jacket: PVC
 Plugs and contacts gold plated,
housing moulded with locking protection on DP side
 DisplayPort v1.2 compliant
 Supports resolutions up to 4096 x 2160 Pixel (4k2k)
 Supports HDCP 1.3 and DPCP

Technical properties

3D	False
ARC	False
Backwards compatible	False
CEC	False
Cable set	False
Chip	False
Compliant with	not specified
Connection type connection 1	Plug
Connection type connection 2	Plug

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.



DATASHEET

Mini DisplayPort – DisplayPort Cable, M-M, 3m, black

Connector 1 angulation	180°
Connector 2 angulation	180°
DSC	False
Dust cover	false
HDMI Power	False
HDMI certified	False
HEC (Ethernet channel)	False
Halogenfree	No
Kink protection	False
MSA	False
MST	False
Model	Round Cable
Number of poles connection 1	20
Number of poles connection 2	19
PCIe Data transfer	False
Shielded	True
Temperature	-20 – 60 °C
Tensile strength (short/long)	39,2 N
Type of connector connection 1	DP
Type of connector connection 2	Mini DisplayPort
Type of packaging	not specified
VESA certified	False
VRR	False
With termination resistor	False
eARC	False

Available variants

ArtNr.	Bezeichnung	Colour	Length	Diameter	AWG
K5565SW.3	Mini DisplayPort – DisplayPort Cable, M-M, 3m, black	black	3.0 m	5.0 mm	32AWG

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

