
DATASHEET

RJ45 Patch Cord Cat.6A S/FTP LSZH Draka UC900 TM21 blue 20m



General data

This Cat.6A (TIA) data cable from the EFB-Elektronik brand transmits data up to 10Gbit. The S/FTP shielding reliably protects against interference and ensures good signal quality. Since it is a Cat.6A (TIA) data cable, it offers a frequency range up to 500MHz, which provides high data transmission performance.

• Increase interference immunity in electromagnetically charged environments – double shielding (S/FTP) improves EMC reserve, reduces susceptibility to radiation and stabilizes transmission in parallel cable routing.
• Cover fire protection requirements in compliance with standards – flame-retardant cable behaviour according to IEC60332-1 reduces the spread of fire in the event of a fault and supports compliance with common installation specifications.
• Power and connect end devices via one cable – reduces cabling effort because data and power are transmitted via 4PPoE according to IEEE802.3bt on one line (fewer power supplies/sockets, faster installation).

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

DATASHEET

RJ45 Patch Cord Cat.6A S/FTP LSZH Draka UC900 TM21 blue 20m

Product Description
The S/FTP data cable has double shielding, which effectively reduces electromagnetic interference. It can be used in a temperature range of -20 – 60 °C. The wide range of possible applications is supported by the bending radius of >25 mm. The LAN cable is IP20 rated. The LSZH jacket is halogen-free and low-smoke. In the event of a fire, it minimizes smoke development and increases indoor safety.

Technical details
• Cat.6A (TIA)
• Connector: RJ45 8(8) to RJ45 8(8) with red TM21 connectors
• Shielding: S/FTP cable with 4x2 x AWG26/7
• Cable shape: round
• Pin assignment: 1:1 according to TIA/EIA 568B
• Equivalent to PoE class: PoE to IEEE802.3af, PoE+ to IEEE802.3at, and 4PPoE to IEEE802.3bt
• Gold-plated contacts
• Sheath: LSZH sheath material
• Outer diameter: 5.9 mm
• With an attached anti-kink grommet
• Fire protection: flame-retardant according to IEC60332-1, low-smoke according to IEC61034, halogen-free according to IEC60754-2
• Degree of protection: IP20
• With a 360° umbrella attachment
• With locking lever protection
• Mating cycles: ≥750
• Brand: EFB-Elektronik

Technical properties	
AWG-size	26/7
Allocation	acc. TIA/EIA 568B
Anti-kink sleeve	put-on
Area of Application	Industrial Ethernet
Bandwidth	500MHz
Bending radius	>25 mm
Cable construction	4x2
Cable shape	rund
Cable type	S/FTP
Cabling standard	EN50173
Category	6A (TIA)
Colour anti-kink sleeve	blue
Colour outer sheath	blue
Conductive shield	360° shield contact
Conductor Material	Copper

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld
fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50
info@efb-elektronik.de
www.efb-elektronik.de

DATASHEET

RJ45 Patch Cord Cat.6A S/FTP LSZH Draka UC900 TM21 blue 20m

Conductor resistance DC	170 Ω/km
Connector	IEC 60603-7-51
Connector type	TM21 red
Contacts	Gold plated
Current capacity	max. 1 A
Euro class	Eca
Fire retardant version	acc. IEC60332-1
Halogen free	acc. IEC60754-2
Harmonised Standard	EN 50575
Impedance	100 ±25 Ω
Insulation Resistance	> 2000 MΩ
Length imprint	False
Locking lever	True
Loop resistance	< 340 Ω/km
Low smoke	acc. IEC61034
Material outer sheath	LSZH
Mating cycles	≥750
Model	shielded
NVP value	79 %
Oil resistant	no
Operating Temperature	-20 – 60 °C
Operating-/ tempering voltage	max. 50 V DC
Outer diameter of the cable	5.9 mm
Ozone resistance	No
Pin assignment	1:1
Raw cable	Cat.7
Resistance unbalance	3 %
Resistant to chemicals	False
Suitable for degree of protection (IP)	IP20
Test voltage	1000 (V DC, 1min) core/core und core/screen
Total screening	ca. 45 %
Transmission	10Gbit
Type of connector connection 1	RJ45 8(8)
Type of connector connection 2	RJ45 8(8)
UL approbated	False
UV resistant	Nein

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

DATASHEET

RJ45 Patch Cord Cat.6A S/FTP LSZH Draka UC900 TM21 blue 20m

Available variants

ArtNr.	Bezeichnung	Length	POE class	Length tolerance
K8054.0,15	RJ45 Patch Cord Cat.6A S/FTP LSZH Draka UC900 TM21 blue 0,15m	0.15 m	PoE acc. to IEEE802.3af;PoE acc. to IEEE802.3at;4PPoE acc. to IEEE802.3bt	±5 %
K8054.0,50	RJ45 Patch Cord Cat.6A S/FTP LSZH Draka UC900 TM21 blue 0,5m	0.5 m	PoE acc. to IEEE802.3af;PoE acc. to IEEE802.3at;4PPoE acc. to IEEE802.3bt	±5 %
K8054.025	RJ45 Patch Cord Cat.6A S/FTP LSZH Draka UC900 TM21 blue 0,25m	0.25 m	PoE acc. to IEEE802.3af;PoE acc. to IEEE802.3at;4PPoE acc. to IEEE802.3bt	±5 %
K8054.1	RJ45 Patch Cord Cat.6A S/FTP LSZH Draka UC900 TM21 blue 1m	1.0 m	PoE acc. to IEEE802.3af;PoE acc. to IEEE802.3at;4PPoE acc. to IEEE802.3bt	±5 %
K8054.1,5	RJ45 Patch Cord Cat.6A S/FTP LSZH Draka UC900 TM21 blue 1,5m	1.5 m	PoE acc. to IEEE802.3af;PoE acc. to IEEE802.3at;4PPoE acc. to IEEE802.3bt	±5 %
K8054.10	RJ45 Patch Cord Cat.6A S/FTP LSZH Draka UC900 TM21 blue 10m	10.0 m	PoE acc. to IEEE802.3af;PoE acc. to IEEE802.3at;4PPoE acc. to IEEE802.3bt	±5 %
K8054.15	RJ45 Patch Cord Cat.6A S/FTP LSZH Draka UC900 TM21 blue 15m	15.0 m	PoE acc. to IEEE802.3af;PoE acc. to IEEE802.3at	±5 %
K8054.2	RJ45 Patch Cord Cat.6A S/FTP LSZH Draka UC900 TM21 blue 2m	2.0 m	PoE acc. to IEEE802.3af;PoE acc. to IEEE802.3at;4PPoE acc. to IEEE802.3bt	±5 %
K8054.20	RJ45 Patch Cord Cat.6A S/FTP LSZH Draka UC900 TM21 blue 20m	20.0 m	PoE acc. to IEEE802.3af;PoE acc. to IEEE802.3at	±5 %
K8054.25	RJ45 Patch Cord Cat.6A S/FTP LSZH Draka UC900 TM21 blue 25m	25.0 m	PoE acc. to IEEE802.3af	±5 %
K8054.3	RJ45 Patch Cord Cat.6A S/FTP LSZH Draka UC900 TM21 blue 3m	3.0 m	PoE acc. to IEEE802.3af;PoE acc. to IEEE802.3at;4PPoE acc. to IEEE802.3bt	±5 %
K8054.30	RJ45 Patch Cord Cat.6A S/FTP LSZH Draka UC900 TM21 blue 30m	30.0 m	PoE acc. to IEEE802.3af	±5 %
K8054.40	RJ45 Patch Cord Cat.6A S/FTP LSZH Draka UC900 TM21 blue 40m	40.0 m	No	±5 %
K8054.5	RJ45 Patch Cord Cat.6A S/FTP LSZH Draka UC900 TM21 blue 5m	5.0 m	PoE acc. to IEEE802.3af;PoE acc. to IEEE802.3at;4PPoE acc. to IEEE802.3bt	±5 %
K8054.50	RJ45 Patch Cord Cat.6A S/FTP LSZH Draka UC900 TM21 blue 50m	50.0 m	No	±5 %
K8054.7,5	RJ45 Patch Cord Cat.6A S/FTP LSZH Draka UC900 TM21 blue 7,5m	7.5 m	PoE acc. to IEEE802.3af;PoE acc. to IEEE802.3at;4PPoE acc. to IEEE802.3bt	±5 %

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION