
DATASHEET

RJ45 Patch Cord Cat.5e F/UTP LSZHDraka UC300 TM11 red 50m



General data

This Cat.5e patch cable from EFB-Elektronik supports 2.5Gbit. The F/UTP shielding reliably protects against interference and ensures good signal quality. Since it is a Cat.5e data cable, it supports a frequency range of up to 100MHz.

• Cover fire protection requirements in compliance with standards – flame-retardant cable behaviour according to IEC60332-1 reduces the spread of fire in the event of a fault and supports compliance with common installation specifications.
• Power and connect devices via a cable – reduces cabling effort because data and power are transmitted via 4PPoE to IEEE802.3bt on a single line. 4PPoE according to IEEE802.3bt can only be used up to certain cable lengths.
• Increased safety in the event of a fire – low smoke development after IEC61034 helps to keep escape routes as low as possible in the event of a fire, and the halogen-free materials according to IEC60754-2 reduce the development of

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

RJ45 Patch Cord Cat.5e F/UTP LSZHDraka UC300 TM11 red 50m

corrosive fire gases.

Product Description
The foil shield of this F/UTP data cable minimizes external interference, improves transmission stability and supports consistent network performance. The temperature range of the cable is -20 – 60 °C. The wide range of possible applications is supported by the bending radius of >20 mm. The Ethernet cable is IP20 rated. The LSZH jacket is halogen-free and low-smoke. In the event of a fire, it minimizes smoke development and increases indoor safety.

Technical details
• Cat.5e
• Connector: RJ45 8(8) to RJ45 8(8) with TM11 connectors
• Shielding: F/UTP cable with 4x2 x AWG26/7
• Cable shape: round
• Pin assignment: 1:1 according to TIA/EIA 568B
• Equivalent to PoE class: PoE to IEEE802.3af, PoE+ to IEEE802.3at, and 4PPoE to IEEE802.3bt
• Gold-plated contacts
• Sheath: LSZH sheath material
• Outer diameter: 5.4 mm
• With an attached anti-kink grommet
• Fire protection: flame-retardant according to IEC60332-1, low-smoke according to IEC61034, halogen-free according to IEC60754-2
• Degree of protection: IP20
• With a 360° umbrella attachment
• Mating cycles: ≥750
• Brand: EFB-Elektronik

Technical properties	
AWG-size	26/7
Allocation	acc. TIA/EIA 568B
Anti-kink sleeve	put-on
Area of Application	Industrial Ethernet
Bandwidth	100MHz
Bending radius	>20 mm
Cable construction	4x2
Cable shape	rund
Cable type	F/UTP
Cable type acc. to Manufacturer	Draka UC300 S26
Cabling standard	EN50173
Category	5e
Colour anti-kink sleeve	red
Colour outer sheath	red

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

DATASHEET

RJ45 Patch Cord Cat.5e F/UTP LSZHDraka UC300 TM11 red 50m

Conductive shield	360° shield contact
Conductor Material	Copper
Conductor resistance DC	130 Ω/km
Connector	IEC 60603-7-3
Connector type	TM11
Contacts	Gold plated
Current capacity	max. 1 A
Fire retardant version	acc. IEC60332-1
Halogen free	acc. IEC60754-2
Harmonised Standard	EN 50575
Impedance	100 ±15 Ω
Insulation Resistance	> 2000 MΩ
Length imprint	False
Locking lever	False
Loop resistance	< 260 Ω/km
Low smoke	acc. IEC61034
Material outer sheath	LSZH
Mating cycles	≥750
Model	shielded
NVP value	67 %
Oil resistant	no
Operating Temperature	-20 – 60 °C
Operating-/ tempering voltage	max. 50 V DC
Outer diameter of the cable	5.4 mm
Ozone resistance	No
Pin assignment	1:1
Resistance unbalance	3 %
Resistant to chemicals	False
Suitable for degree of protection (IP)	IP20
Test voltage	1000 (V DC, 1min) core/core und core/screen
Transmission	2.5Gbit
Type of connector connection 1	RJ45 8(8)
Type of connector connection 2	RJ45 8(8)
UL approbated	False
UV resistant	Nein

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

DATASHEET

RJ45 Patch Cord Cat.5e F/UTP LSZHDraka UC300 TM11 red 50m

Available variants

ArtNr.	Bezeichnung	Length	POE class	Length tolerance
K8076.0,15	RJ45 Patch Cord Cat.5e F/UTP LSZH Draka UC300 TM11 red 0.15m	0.15 m	PoE acc. to IEEE802.3af;PoE+ acc. to IEEE802.3at;4PPoE acc. to IEEE802.3bt	±5 %
K8076.0,25	RJ45 Patch Cord Cat.5e F/UTP LSZHDraka UC300 TM11 red 0,25m	0.25 m	PoE acc. to IEEE802.3af;PoE+ acc. to IEEE802.3at;4PPoE acc. to IEEE802.3bt	±5 %
K8076.0,50	RJ45 Patch Cord Cat.5e F/UTP LSZHDraka UC300 TM11 red 0,5m	0.5 m	PoE acc. to IEEE802.3af;PoE+ acc. to IEEE802.3at;4PPoE acc. to IEEE802.3bt	±5 %
K8076.1	RJ45 Patch Cord Cat.5e F/UTP LSZHDraka UC300 TM11 red 1m	1.0 m	PoE acc. to IEEE802.3af;PoE+ acc. to IEEE802.3at;4PPoE acc. to IEEE802.3bt	±5 %
K8076.1,5	RJ45 Patch Cord Cat.5e F/UTP LSZHDraka UC300 TM11 red 1,5m	1.5 m	PoE acc. to IEEE802.3af;PoE+ acc. to IEEE802.3at;4PPoE acc. to IEEE802.3bt	±5 %
K8076.10	RJ45 Patch Cord Cat.5e F/UTP LSZHDraka UC300 TM11 red 10m	10.0 m	PoE acc. to IEEE802.3af;PoE+ acc. to IEEE802.3at;4PPoE acc. to IEEE802.3bt	±5 %
K8076.15	RJ45 Patch Cord Cat.5e F/UTP LSZHDraka UC300 TM11 red 15m	15.0 m	PoE acc. to IEEE802.3af;PoE+ acc. to IEEE802.3at;4PPoE acc. to IEEE802.3bt	±5 %
K8076.2	RJ45 Patch Cord Cat.5e F/UTP LSZHDraka UC300 TM11 red 2m	2.0 m	PoE acc. to IEEE802.3af;PoE+ acc. to IEEE802.3at;4PPoE acc. to IEEE802.3bt	±5 %
K8076.25	RJ45 Patch Cord Cat.5e F/UTP LSZHDraka UC300 TM11 red 25m	25.0 m	PoE acc. to IEEE802.3af;PoE+ acc. to IEEE802.3at	±5 %
K8076.3	RJ45 Patch Cord Cat.5e F/UTP LSZHDraka UC300 TM11 red 3m	3.0 m	PoE acc. to IEEE802.3af;PoE+ acc. to IEEE802.3at;4PPoE acc. to IEEE802.3bt	±5 %
K8076.30	RJ45 Patch Cord Cat.5e F/UTP LSZHDraka UC300 TM11 red 30m	30.0 m	PoE acc. to IEEE802.3af;PoE+ acc. to IEEE802.3at	±5 %
K8076.40	RJ45 Patch Cord Cat.5e F/UTP LSZHDraka UC300 TM11 red 40m	40.0 m	PoE acc. to IEEE802.3af	±5 %
K8076.5	RJ45 Patch Cord Cat.5e F/UTP LSZHDraka UC300 TM11 red 5m	5.0 m	PoE acc. to IEEE802.3af;PoE+ acc. to IEEE802.3at;4PPoE acc. to IEEE802.3bt	±5 %
K8076.50	RJ45 Patch Cord Cat.5e F/UTP LSZHDraka UC300 TM11 red 50m	50.0 m	No	±5 %
K8076.7,5	RJ45 Patch Cord Cat.5e F/UTP LSZHDraka UC300 TM11 red 7,5m	7.5 m	PoE acc. to IEEE802.3af;PoE+ acc. to IEEE802.3at;4PPoE acc. to IEEE802.3bt	±5 %

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION