


DATASHEET

RJ45 Patch Cord Cat.5e U/UTP PVC CCA magenta 0,5m



General data

This Cat.5e LAN cable from EFB-Elektronik transmits data up to 2.5Gbit. Because it is a Cat.5e data cable, it offers a frequency range of up to 100MHz.

- Cover fire protection requirements in compliance with standards – flame-retardant cable behaviour according to IEC60332-1 reduces the spread of fire in the event of a fault and supports compliance with common installation specifications.
- Ensure reliable 2.5 Gigabit connections – gold-plated contact surfaces reduce contact resistances and contact corrosion, which supports signal quality and thus stable 2.5 Gbps transmission.
- Reliable 100MHz bandwidth performance ensures high-speed data transmission.

Product Description

The unshielded design in this U/UTP patch cable enables cost-efficient networking in low-interference environments while providing high flexibility for easy installation. The temperature range of the cable is -20 – 60 °C. The wide range of possible applications is supported by the bending radius of >27 mm. The patch cord is IP20 rated. The polyvinyl chloride (PVC) jacket is a flexible standard jacket for network applications, without special fire protection properties.

Technical details

- Cat.5e
- Connector: RJ45 8(8) to RJ45 8(8) with RJ45 connectors
- Shielding: U/UTP cable with 4x2 x AWG24/7

This datasheet was created automatically on 13-09-2026 . Technical changes reserved.



DATASHEET

RJ45 Patch Cord Cat.5e U/UTP PVC CCA magenta 0,5m

- Pin assignment: 1:1 according to TIA/EIA 568B
- Gold-plated contacts
- Sheath: Polyvinyl chloride (PVC) sheath material
- Outer diameter: 5.4 mm
- With an injected anti-kink grommet
- Fire protection: flame-retardant according to IEC60332-1
- Degree of protection: IP20
- Mating cycles: ≥ 750
- With length print
- Brand: EFB-Elektronik

Technical properties

AWG-size	24/7
Allocation	acc. TIA/EIA 568B
Anti-kink sleeve	moulded-on
Area of Application	Industrial Ethernet
Bandwidth	100MHz
Bending radius	>27 mm
Cable construction	4x2
Cable type	U/UTP
Cabling standard	EN50173
Category	5E
Colour anti-kink sleeve	magenta
Colour outer sheath	magenta
Conductive shield	Nein
Conductor Material	CCA
Connector	IEC 60603-7-2
Connector type	RJ45 Standard
Contact Resistance	< 20 mΩ
Contacts	Vergoldet
Current capacity	max. 1 A
Fire retardant version	acc. IEC60332-1
Halogen free	No
Impedance	100
Length imprint	True
Locking lever	False
Material outer sheath	Polyvinyl chloride (PVC)
Mating cycles	≥ 750
Model	ungeschirmt
Oil resistant	no

This datasheet was created automatically on 13-09-2026 . Technical changes reserved.



DATASHEET

RJ45 Patch Cord Cat.5e U/UTP PVC CCA magenta 0,5m

Operating Temperature	-20 – 60 °C
Operating-/ tempering voltage	max. 50 V DC
Outer diameter of the cable	5.4 mm
Ozone resistance	No
Pin assignment	1:1
Printing	UTP Cat.5E 100MHZ 24AWGX4P Patch ISO/IEC 11801 & EN 50173 verified www.efb-elektronik.de
Resistant to chemicals	False
Silicone-free	True
Suitable for degree of protection (IP)	IP20
Test voltage	1000 (V DC, 1min) core/core und core/screen
Transmission	2.5Gbit
Type of connector connection 1	RJ45 8(8)
Type of connector connection 2	RJ45 8(8)

Available variants

ArtNr.	Bezeichnung	Length POE class		Length tolerance
K8091.0,5	RJ45 Patch Cord Cat.5e U/UTP PVC CCA magenta 0,5m	0.5 m	No	±5 %
K8091.1	RJ45 Patch Cord Cat.5e U/UTP PVC CCA magenta 1m	1.0 m	No	±5 %
K8091.10	RJ45 Patch Cord Cat.5e U/UTP PVC CCA magenta 10m	10.0 m	No	±5 %
K8091.2	RJ45 Patch Cord Cat.5e U/UTP PVC CCA magenta 2m	2.0 m	No	±5 %
K8091.3	RJ45 Patch Cord Cat.5e U/UTP PVC CCA magenta 3m	3.0 m	No	±5 %
K8091.30	RJ45 Patch Cord Cat.5e U/UTP PVC CCA magenta 30m	30.0 m	No	±5 %
K8091.5	RJ45 Patch Cord Cat.5e U/UTP PVC CCA magenta 5m	5.0 m	No	±5 %
K8091.7,5	RJ45 Patch Cord Cat.5e U/UTP PVC CCA magenta 7,5m	7.5 m	No	±5 %

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 13-09-2026 . Technical changes reserved.

