

# DATASHEET

## RJ45 Patch Cord Cat.5e U/UTP PVC CCA blue 5m



### General data

The Cat.5e LAN cable from EFB-Elektronik supports data transfers up to 2.5Gbit. Since it is a Cat.5e data cable, it offers a frequency range up to 100MHz.

- Cover fire protection requirements in compliance with standards – flame-retardant cable behaviour according to IEC60332-1 reduces the spread of fire in the event of a fault and supports compliance with common installation specifications.
- Ensure reliable 2.5 Gigabit connections – gold-plated contact surfaces reduce contact resistances and contact corrosion, which supports signal quality and thus stable 2.5 Gbps transmission.
- Reliable 100MHz bandwidth performance ensures high-speed data transmission.

### Product Description

The unshielded design in this U/UTP patch cable enables cost-efficient networking in low-interference environments while providing high flexibility for easy installation. The temperature range of the cable is -20 – 60 °C. The wide range of possible applications is supported by the bending radius of >27 mm. The data cable has an IP20 rating. The polyvinyl chloride (PVC) jacket is a flexible standard jacket for network applications, without special fire protection properties.

### Technical details

- Cat.5e
- Connector: RJ45 8(8) to RJ45 8(8) with RJ45 connectors

This datasheet was created automatically on 21-09-2026 . Technical changes reserved.

# DATASHEET

## RJ45 Patch Cord Cat.5e U/UTP PVC CCA blue 5m

- Shielding: U/UTP cable with 4x2 x AWG24/7
- Pin assignment: 1:1 according to TIA/EIA 568B
- Gold-plated contacts
- Sheath: Polyvinyl chloride (PVC) sheath material
- Outer diameter: 5.4 mm
- With an injected anti-kink grommet
- Fire protection: flame-retardant according to IEC60332-1
- Degree of protection: IP20
- Mating cycles:  $\geq 750$
- With length print
- Brand: EFB-Elektronik

### Technical properties

|                         |                        |
|-------------------------|------------------------|
| AWG-size                | 24/7                   |
| Allocation              | acc. TIA/EIA 568B      |
| Anti-kink sleeve        | moulded-on             |
| Area of Application     | Industrial Ethernet    |
| Bandwidth               | 100MHz                 |
| Bending radius          | >27 mm                 |
| Cable construction      | 4x2                    |
| Cable type              | U/UTP                  |
| Cabling standard        | EN50173                |
| Category                | 5e                     |
| Colour anti-kink sleeve | blue                   |
| Colour outer sheath     | blue                   |
| Conductive shield       | No                     |
| Conductor Material      | CCA                    |
| Connector               | IEC 60603-7-2          |
| Connector type          | RJ45 standard          |
| Contact Resistance      | < 20 mΩ                |
| Contacts                | Gold plated            |
| Current capacity        | max. 1 A               |
| Fire retardant version  | acc. IEC60332-1        |
| Halogen free            | No                     |
| Impedance               | 100                    |
| Length imprint          | True                   |
| Locking lever           | False                  |
| Material outer sheath   | Polyvinylchlorid (PVC) |
| Mating cycles           | $\geq 750$             |
| Model                   | unshielded             |

This datasheet was created automatically on 21-09-2026 . Technical changes reserved.



# DATASHEET

## RJ45 Patch Cord Cat.5e U/UTP PVC CCA blue 5m

|                                        |                                                                                                                                     |
|----------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------|
| Oil resistant                          | no                                                                                                                                  |
| Operating Temperature                  | -20 - 60 °C                                                                                                                         |
| Operating-/ tempering voltage          | max. 50 V DC                                                                                                                        |
| Outer diameter of the cable            | 5.4 mm                                                                                                                              |
| Ozone resistance                       | No                                                                                                                                  |
| Pin assignment                         | 1:1                                                                                                                                 |
| Printing                               | UTP Cat.5E 100MHZ 24AWGX4P Patch ISO/IEC 11801 & EN 50173 verified <a href="http://www.efb-elektronik.de">www.efb-elektronik.de</a> |
| Resistant to chemicals                 | False                                                                                                                               |
| Silicone-free                          | True                                                                                                                                |
| Suitable for degree of protection (IP) | IP20                                                                                                                                |
| Test voltage                           | 1000 (V DC, 1min) core/core und core/screen                                                                                         |
| Transmission                           | 2.5Gbit                                                                                                                             |
| Type of connector connection 1         | RJ45 8(8)                                                                                                                           |
| Type of connector connection 2         | RJ45 8(8)                                                                                                                           |

### Available variants

| ArtNr.   | Bezeichnung                                   | Length | POE class | Length tolerance |
|----------|-----------------------------------------------|--------|-----------|------------------|
| K8094.10 | RJ45 Patch Cord Cat.5e U/UTP PVC CCA blue 10m | 10.0 m | No        | ±5 %             |
| K8094.3  | RJ45 Patch Cord Cat.5e U/UTP PVC CCA blue 3m  | 3.0 m  | No        | ±5 %             |
| K8094.5  | RJ45 Patch Cord Cat.5e U/UTP PVC CCA blue 5m  | 5.0 m  | No        | ±5 %             |

### Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 21-09-2026 . Technical changes reserved.

