


DATASHEET

RJ45 Patch Cord Cat.6A U/UTP TPE3,6mm ultraflex black 5m



General data

This Cat.6A (TIA) Ethernet cable from EFB-Elektronik transmits data up to 10Gbit. Since it is a Cat.6A (TIA) data cable, it supports a frequency range of up to 500MHz, which provides high data transmission performance.

- Slim cable – the extra-thin cable construction with an outer diameter of 3.6 mm makes the patch cable particularly suitable for areas with limited space or hard-to-reach areas.
- Cover fire protection requirements in compliance with standards – flame-retardant cable behaviour according to IEC60332-1 reduces the spread of fire in the event of a fault and supports compliance with common installation specifications.
- Power and connect end devices via one cable – reduces cabling effort because data and power are transmitted via PoE+ to IEEE802.3at on one line (fewer power adapters/sockets, faster installation).

This datasheet was created automatically on 23-09-2026 . Technical changes reserved.



DATASHEET

RJ45 Patch Cord Cat.6A U/UTP TPE3,6mm ultraflex black 5m

Product Description

The unshielded design in this U/UTP Ethernet cable enables cost-effective networking in low-interference environments while providing high flexibility for easy installation. The temperature range of the cable is -20 – 60 °C. The wide range of possible applications is supported by the bending radius of >15 mm. The patch cable has an IP20 rating. The TPE/LSZH jacket is flexible, halogen-free and low-smoke, making it ideal for safe and professional patch and server cabinet installations.

Technical details

- Cat.6A (TIA)
- Connector: RJ45 8(8) to RJ45 8(8) with extra-short RJ45 connectors
- Shielding: U/UTP cable with 4x2 x AWG30/7
- Cable shape: slim
- Pin assignment: 1:1 according to TIA/EIA 568B
- Corresponds to PoE class: PoE according to IEEE802.3af and PoE+ according to IEEE802.3at
- Gold-plated contacts
- Sheath: TPE/LSZH sheath material
- Outer diameter: 3.6 mm
- With an injected anti-kink grommet
- Fire protection: flame-retardant according to IEC60332-1, low-smoke according to IEC61034, halogen-free according to IEC60754-2
- Degree of protection: IP20
- With locking lever protection
- Mating cycles: ≥750
- Brand: EFB-Elektronik

Technical properties

AWG-size	30/7
Allocation	acc. TIA/EIA 568B
Anti-kink sleeve	moulded-on
Area of Application	Industrial Ethernet
Bandwidth	500MHz
Bending radius	>15 mm
Cable construction	4x2
Cable shape	slim
Cable type	U/UTP
Cabling standard	EN50173
Category	6A (TIA)
Colour anti-kink sleeve	black
Colour outer sheath	black
Conductive shield	No
Conductor Material	Copper

This datasheet was created automatically on 23-09-2026 . Technical changes reserved.



DATASHEET

RJ45 Patch Cord Cat.6A U/UTP TPE3,6mm ultraflex black 5m

Conductor resistance DC	376 Ω/km
Connector	IEC 60603-7-41
Connector type	RJ45 short version
Contact Resistance	< 20 mΩ
Contacts	Gold plated
Current capacity	max. 1 A
Fire retardant version	acc. IEC60332-1
Halogen free	acc. IEC60754-2
Harmonised Standard	EN 50575
Impedance	100 ±15 Ω
Insulation Resistance	100 MΩ
Length imprint	False
Locking lever	True
Loop resistance	752 Ω/km
Low smoke	acc. IEC61034
Material outer sheath	TPE/LSZH
Mating cycles	≥750
Model	unshielded
NVP value	76 %
Oil resistant	no
Operating Temperature	-20 – 60 °C
Operating-/ tempering voltage	max. 50 V DC
Outer diameter of the cable	3.6 mm
Ozone resistance	No
Pin assignment	1:1
Printing	Cat.6A Patchcord ULTRAFLEX U/UTP TPE 10G
Resistance unbalance	< 4 %
Resistant to chemicals	False
Silicone-free	True
Suitable for degree of protection (IP)	IP20
Test voltage	1000 (V DC, 1min) core/core und core/screen
Transmission	10Gbit
Type of connector connection 1	RJ45 8(8)
Type of connector connection 2	RJ45 8(8)
UL approbated	False
UV resistant	no

This datasheet was created automatically on 23-09-2026 . Technical changes reserved.



DATASHEET

RJ45 Patch Cord Cat.6A U/UTP TPE3,6mm ultraflex black 5m

Available variants

ArtNr.	Bezeichnung	Length POE class		Length tolerance
K8108SW.0,15	RJ45 Patch Cord Cat.6A U/UTP TPE3,6mm ultraflex black 0,15m	0.15 m	PoE acc. to IEEE802.3af;PoE acc. to IEEE802.3at	±5 %
K8108SW.0,25	RJ45 Patch Cord Cat.6A U/UTP TPE3,6mm ultraflex black 0,25m	0.25 m	PoE acc. to IEEE802.3af;PoE acc. to IEEE802.3at	±5 %
K8108SW.0,5	RJ45 Patch Cord Cat.6A U/UTP TPE3,6mm ultraflex black 0,5m	0.5 m	PoE acc. to IEEE802.3af;PoE acc. to IEEE802.3at	±5 %
K8108SW.1	RJ45 Patch Cord Cat.6A U/UTP TPE3,6mm ultraflex black 1m	1.0 m	PoE acc. to IEEE802.3af;PoE acc. to IEEE802.3at	±5 %
K8108SW.1,5	RJ45 Patch Cord Cat.6A U/UTP TPE3,6mm ultraflex black 1,5m	1.5 m	PoE acc. to IEEE802.3af	±5 %
K8108SW.2	RJ45 Patch Cord Cat.6A U/UTP TPE3,6mm ultraflex black 2m	2.0 m	PoE acc. to IEEE802.3af	±5 %
K8108SW.3	RJ45 Patch Cord Cat.6A U/UTP TPE3,6mm ultraflex black 3m	3.0 m	PoE acc. to IEEE802.3af	±5 %
K8108SW.5	RJ45 Patch Cord Cat.6A U/UTP TPE3,6mm ultraflex black 5m	5.0 m	PoE acc. to IEEE802.3af	±5 %

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 23-09-2026 . Technical changes reserved.

