

DATASHEET

Coax C. RG58 2x Plugs straight RG58 C/U 50 Ohm 5.0m



General data

Pre-assembled RG58 coaxial cable for high frequent measured data and signals

Technical properties

Cable type	RG 58
Connection type connection 1	Plug
Connection type connection 2	Plug
Screening	Single shielded
Screening effectiveness	90 dB
Type of connector connection 1	BNC
Type of connector connection 2	BNC

Available variants

ArtNr.	Bezeichnung	Length	Colour	Impedance
K8300.10	Coax C. RG58 2x Plugs straight RG58 C/U 50 Ohm 10.0m	10.0 m	Black	50 Ohm
K8300.3	Coax C. RG58 2x Plugs straight RG58 C/U 50 Ohm 3.0m	3.0 m	Black	50 Ohm
K8300.5	Coax C. RG58 2x Plugs straight RG58 C/U 50 Ohm 5.0m	5.0 m	Black	50 Ohm

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

