

DATASHEET

Coaxial cable RG59 B/U 75 Ohm, 2 x straight plugs, 2.0m



General data

Pre-assembled RG59 coaxial cable for high frequent measured data and signals

Technical properties

Bending radius (dynamic/static)	40 mm
Cable printing	RG59 C/U 75 OHM COAXIAL CABLE
Cable type	RG 59
Compatible with	security systems
Connection type connection 1	Plug
Connection type connection 2	Plug
Connector 1 angulation	180 °
Connector 2 angulation	180 °
Halogen free acc. to EN 50267-2-2	False
Housing material	Zinc die-cast alloy
Jacket material	PVC
Operating temperature	-10 - 60 °C
Outer diameter	6 mm
Scope of delivery	1 x Coax cable
Screening	Single shielded
Screening effectiveness	90 dB
Signal type	Baseband Video Signals, Digital Video Signals, CATV RF Signals
Storage Temperature	-20 - 60 °C
Type of connector connection 1	BNC
Type of connector connection 2	BNC

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.



DATASHEET

Coaxial cable RG59 B/U 75 Ohm, 2 x straight plugs, 2.0m

Warranty	36 months
Wave resistance	75 Ohm

Available variants

ArtNr.	Bezeichnung	Length	Colour	Impedance
K8360.2V2	Coaxial cable RG59 B/U 75 Ohm, 2 x straight plugs, 2.0m	2.0 m	Black	75 Ohm
K8360.3V2	Coaxial cable RG59 B/U 75 Ohm, 2 x straight plugs, 3.0m	3.0 m	Black	75 Ohm
K8360.5V2	Coaxial cable RG59 B/U 75 Ohm, 2 x straight plugs, 5.0m	5.0 m	Black	75 Ohm

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

