




- Increase interference immunity in electromagnetically charged environments – double shielding (S/FTP) improves EMC reserve, reduces susceptibility to radiation and stabilizes transmission in parallel cable routing.
- Cover fire protection requirements in compliance with standards – flame-retardant cable behaviour according to IEC60332-1 reduces the spread of fire in the event of a fault and supports compliance with common installation specifications.
- Power and connect devices via a cable – reduces cabling effort because data and power are transmitted via 4PPoE to IEEE802.3bt on a single line. 4PPoE according to IEEE802.3bt can only be used up to certain cable lengths.



WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION



DATASHEET

RJ45 Patch Cord Cat.6A S/FTP LSZH Draka UC900 TM31 yellow 1m

Product Description

The S/FTP LAN cable has a double shield that effectively minimizes electromagnetic interference. The temperature range of the cable is -20 – 60 °C. The wide range of possible applications is supported by the bending radius of >25 mm. The Ethernet cable has an IP20 rating. The LSZH jacket is halogen-free and low-smoke. In the event of a fire, it minimizes smoke development and increases indoor safety.

Technical details

- Cat.6A (TIA)
- Connector: RJ45 8(8) to RJ45 8(8) with yellow TM31 connectors
- Shielding: S/FTP cable with 4x2 x AWG26/7
- Cable shape: round
- Pin assignment: 1:1 according to TIA/EIA 568B
- Equivalent to PoE class: PoE to IEEE802.3af, PoE+ to IEEE802.3at, and 4PPoE to IEEE802.3bt
- Gold-plated contacts
- Sheath: LSZH sheath material
- Outer diameter: 5.9 mm
- With an attached anti-kink grommet
- Fire protection: flame-retardant according to IEC60332-1, low-smoke according to IEC61034, halogen-free according to IEC60754-2
- Degree of protection: IP20
- With a 360° umbrella attachment
- With locking lever protection
- Mating cycles: ≥750
- Brand: EFB-Elektronik

Technical properties

AWG-size	26/7
Allocation	acc. TIA/EIA 568B
Anti-kink sleeve	put-on
Area of Application	Industrial Ethernet
Bandwidth	500MHz
Bending radius	>25 mm
Cable construction	4x2
Cable shape	rund
Cable type	S/FTP
Cable type acc. to Manufacturer	Draka UC900 SS26
Cabling standard	EN50173
Category	6A (TIA)
Colour anti-kink sleeve	yellow
Colour outer sheath	yellow
Conductive shield	360° shield contact

This datasheet was created automatically on 21-09-2026 . Technical changes reserved.



DATASHEET

RJ45 Patch Cord Cat.6A S/FTP LSZH Draka UC900 TM31 yellow 1m

Conductor Material	Copper
Conductor resistance DC	170 Ω /km
Connector	IEC 60603-7-51
Connector type	TM31 yellow
Contacts	Gold plated
Current capacity	max. 1 A
Euro class	Eca
Fire retardant version	acc. IEC60332-1
Halogen free	acc. IEC60754-2
Harmonised Standard	EN 50575
Impedance	100 $\pm$ 5 Ω
Insulation Resistance	> 2000 M Ω
Length imprint	False
Locking lever	True
Loop resistance	< 340 Ω /km
Low smoke	acc. IEC61034
Material outer sheath	LSZH
Mating cycles	$\geq$ 750
Model	shielded
NVP value	79 %
Oil resistant	no
Operating Temperature	-20 - 60 $^{\circ}$ C
Operating-/ tempering voltage	max. 50 V DC
Outer diameter of the cable	5.9 mm
Ozone resistance	No
Pin assignment	1:1
Raw cable	Cat.7
Resistance unbalance	3 %
Resistant to chemicals	False
Suitable for degree of protection (IP)	IP20
Test voltage	1000 (V DC, 1min) core/core und core/screen
Total screening	ca. 45 %
Transmission	10Gbit
Type of connector connection 1	RJ45 8(8)
Type of connector connection 2	RJ45 8(8)
UL approbated	False

This datasheet was created automatically on 21-09-2026 . Technical changes reserved.



DATASHEET

RJ45 Patch Cord Cat.6A S/FTP LSZH Draka UC900 TM31 yellow 1m

UV resistant	no
--------------	----

Available variants

ArtNr.	Bezeichnung	Length POE class		Length tolerance
K8560GE.0,15	RJ45 Patch Cord Cat.6A S/FTP LSZH Draka UC900 TM31 yellow 0,15m	0.15 m	PoE acc. to IEEE802.3af;PoE acc. to IEEE802.3at;4PPoE acc. to IEEE802.3bt	±5 %
K8560GE.0,25	RJ45 Patch Cord Cat.6A S/FTP LSZH Draka UC900 TM31 yellow 0,25m	0.25 m	PoE acc. to IEEE802.3af;PoE acc. to IEEE802.3at;4PPoE acc. to IEEE802.3bt	±5 %
K8560GE.0,50	RJ45 Patch Cord Cat.6A S/FTP LSZH Draka UC900 TM31 yellow 0,5m	0.5 m	PoE acc. to IEEE802.3af;PoE acc. to IEEE802.3at;4PPoE acc. to IEEE802.3bt	±5 %
K8560GE.1	RJ45 Patch Cord Cat.6A S/FTP LSZH Draka UC900 TM31 yellow 1m	1.0 m	PoE acc. to IEEE802.3af;PoE acc. to IEEE802.3at;4PPoE acc. to IEEE802.3bt	±5 %
K8560GE.1,5	RJ45 Patch Cord Cat.6A S/FTP LSZH Draka UC900 TM31 yellow 1,5m	1.5 m	PoE acc. to IEEE802.3af;PoE acc. to IEEE802.3at	±5 %
K8560GE.10	RJ45 Patch Cord Cat.6A S/FTP LSZH Draka UC900 TM31 yellow 10m	10.0 m	PoE acc. to IEEE802.3af;PoE acc. to IEEE802.3at;4PPoE acc. to IEEE802.3bt	±5 %
K8560GE.15	RJ45 Patch Cord Cat.6A S/FTP LSZH Draka UC900 TM31 yellow 15m	15.0 m	PoE acc. to IEEE802.3af;PoE acc. to IEEE802.3at	±5 %
K8560GE.2	RJ45 Patch Cord Cat.6A S/FTP LSZH Draka UC900 TM31 yellow 2m	2.0 m	PoE acc. to IEEE802.3af;PoE acc. to IEEE802.3at	±5 %
K8560GE.20	RJ45 Patch Cord Cat.6A S/FTP LSZH Draka UC900 TM31 yellow 20m	20.0 m	PoE acc. to IEEE802.3af;PoE acc. to IEEE802.3at	±5 %
K8560GE.25	RJ45 Patch Cord Cat.6A S/FTP LSZH Draka UC900 TM31 yellow 25m	25.0 m	PoE acc. to IEEE802.3af	±5 %
K8560GE.3	RJ45 Patch Cord Cat.6A S/FTP LSZH Draka UC900 TM31 yellow 3m	3.0 m	PoE acc. to IEEE802.3af;PoE acc. to IEEE802.3at;4PPoE acc. to IEEE802.3bt	±5 %
K8560GE.30	RJ45 Patch Cord Cat.6A S/FTP LSZH Draka UC900 TM31 yellow 30m	30.0 m	PoE acc. to IEEE802.3af	±5 %
K8560GE.40	RJ45 Patch Cord Cat.6A S/FTP LSZH Draka UC900 TM31 yellow 40m	40.0 m	No	±5 %
K8560GE.5	RJ45 Patch Cord Cat.6A S/FTP LSZH Draka UC900 TM31 yellow 5m	5.0 m	PoE acc. to IEEE802.3af;PoE acc. to IEEE802.3at;4PPoE acc. to IEEE802.3bt	±5 %
K8560GE.50	RJ45 Patch Cord Cat.6A S/FTP LSZH Draka UC900 TM31 yellow 50m	50.0 m	No	±5 %
K8560GE.7,5	RJ45 Patch Cord Cat.6A S/FTP LSZH Draka UC900 TM31 yellow 7,5m	7.5 m	PoE acc. to IEEE802.3af;PoE acc. to IEEE802.3at;4PPoE acc. to IEEE802.3bt	±5 %

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 21-09-2026 . Technical changes reserved.

