

DATASHEET

Hook & Loop Cable Tie, 10piec./bag, black, lenght 160mm, wight 12mm



General data

Perfect bundling for all kind of cables
 Toolfree and stressfree for any cable type
 Recommended especially for fiber optic cables
 Resolvable without problems at any time
 With slot
 Hook-and-loop cable ties in 10 pieces bag

Technical properties

Adhesive surface	False
Band closure	Hook-and-loop fastener
Fluorescent	False
Halogen free	No
MIL approval	False
Material	Plastic
Material quality	Polyamide (PA)
Model	Hook-and-loop fastener tape
Mounting temperature	-10 - 60 °C
Number of pieces per pack	10
Operating temperature	-10 - 60 °C
Packaging type	Poly byg
Scope of delivery	Cable ties
Solvable fastener	True
Surface treatment	Plastic-coated

This datasheet was created automatically on 30-09-2026 . Technical changes reserved.



DATASHEET

Hook & Loop Cable Tie, 10piec./bag, black, lenght 160mm, wight 12mm

Text strip	None
Type of fastening	Other
UL approval	False
UV-stable according to ASTM D6779	False
VG approval	False
Warranty	12month

Available variants

ArtNr.	Bezeichnung	Band width	Colour	Length belt/tape/tie	Operating temperature	Transparent	Tie thickness	Max. bundle diameter
KB12-130B	Hook & Loop Cable Tie, 10piec./bag, black, lenght 130mm, wight 12mm	12 mm	Black	130 m	-5 – 70 °C	False	1.45 mm	- mm
KB12-160B	Hook & Loop Cable Tie, 10piec./bag, black, lenght 160mm, wight 12mm	12 mm	Black	160 m	-5 – 70 °C	False	1.45 mm	- mm
KB12-230B	Hook & Loop Cable Tie, 10piec./bag, black, lenght 230mm, wight 12mm	12 mm	Black	230 m	-5 – 70 °C	False	1.45 mm	- mm

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 30-09-2026 . Technical changes reserved.

