

DATASHEET

Hook & Loop Tape, 20mm black, 25m Roll



General data

Ultra slim construction
 Reusable
 Hook and strip material: Polyamide
 Colour: black
25 m on rolls

Technical properties

Band closure	Hook-and-loop fastener
Fluorescent	False
Halogen free	No
MIL approval	False
Material	Plastic
Material quality	Polyamide (PA)
Model	Hook-and-loop fastener tape
Mounting temperature	-10 - 60 °C
Operating temperature	-10 - 60 °C
Solvable fastener	True
Surface treatment	Plastic-coated
Text strip	None
Type of fastening	Other
UL approval	False
UV-stable according to ASTM D6779	False
VG approval	False

This datasheet was created automatically on 17-09-2026 . Technical changes reserved.



DATASHEET

Hook & Loop Tape, 20mm black, 25m Roll

Available variants

ArtNr.	Bezeichnung	Band width	Colour	Length belt/tape/tie	Transparent	Tie thickness	Max. bundle diameter
KB20-2500B	Hook & Loop Tape, 20mm black, 25m Roll	20 mm	black	25000 m	False	1.45 mm	230 mm

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 17-09-2026 . Technical changes reserved.

