


DATASHEET

Keystone Modul LC/APC Duplex OS2 grün,



General data

LC duplex connectors in colored plastic housings with ceramic sleeves. Flangeless connectors allow for higher packing densities and can be used as Keystone modules in combination with the Keystone frame.

Technical properties

Colour Dust Cover	White
Conform to Standard	IEC61754-20
Construction type	SC-Simplex
Dust cover	True
Height	9.3 mm
Internal Shutter	False
Length	29.2 mm
Material housing	Plastic
Material sleeve	Ceramics
Operating temperature	-40 - 75 °C
Packaging	Polybag
Storage Temperature	-40 - 85 °C
Type of connector connection 1	LC-Duplex

This datasheet was created automatically on 18-09-2026 . Technical changes reserved.



DATASHEET

Keystone Modul LC/APC Duplex OS2 grün,

Type of connector connection 2	LC-Duplex
Type of fastening	Engage (snap)
Type of housing	flangeless
Type of locking	Latching mechanism
Width	15.2 mm

Available variants

ArtNr.	Bezeichnung	Unique
KM53519	Keystone Modul LC/APC Duplex OS2 grün,	Unique

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 18-09-2026 . Technical changes reserved.

