
DATASHEET

INFRALAN® Cat.7A 1200 AWG22, S/FTP 4P CPR B2ca orange RAL 2003



General data

The INFRALAN Cat.7A S/FTP halogen-free installation cable in orange is designed for high-performance network cabling. The S/FTP structure with braid and the FRNC-B sheath support stable data connections up to 1200 MHz and are therefore suitable for modern installations with high bandwidth. The halogen-free version according to EN 60754-1/2 and the classification according to RoHS 2011/65/UE complement the cable with a contemporary choice of material.

• 1200 MHz Cat.7A bandwidth – Supports transmission standards from IEEE 802.3 10Mbit to 10Gbit and creates scope for high-performance networks.
• S/FTP setup with braided shielding – Reduces interference and supports stable signal quality in demanding cabling.
• FRNC-B jacket in orange with RAL 2003 and CPR B2ca – Combines the halogen-free version according to EN 60754-1/2 with a clear marking for modern installations.

The simplex cable uses 22/1 conductors with 8 wires. The dynamic bending radius of 40 mm facilitates installation and the braided shielding supports decoupling from external influences. The version without reinforcement is intended for PoE according to IEEE802.3af, PoE+ according to IEEE802.3at and 4PPoE according to IEEE802.3bt and complies with RoHS 2011/65/UE.

Technical details

This datasheet was created automatically on 18-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

DATASHEET

INFRALAN® Cat.7A 1200 AWG22, S/FTP 4P CPR B2ca orange RAL 2003

- Brand: INFRALAN
- Category: 7A
- Transmission standards: IEEE 802.3 10Mbit to 10Gbit
- Max. frequency: 1200 MHz
- Cable construction: S/FTP
- PoE: after IEEE802.3af PoE, after IEEE802.3at PoE+, after IEEE802.3bt 4PPoE
- AWG cross-section/number of wires: 22/1
- Number of cores: 8
- Type: simplex
- Sheath material: FRNC-B
- Sheath colour: orange
- RAL colour: RAL 2003
- Armour: without
- Bend radius (dynamic): 40 mm
- Directive/Regulation: RoHS 2011/65/UE
- Euroclass: B2ca
- Halogen-free: according to EN 60754-1/2
- Shield over stranding: braid

Technical properties	
AWG-size	22/1
Armour	none
Bending radius (dynamic)	40 mm
Cable	IEC 61156-6
Cable silicone free	True
Cable structure	S/FTP
Cable type	EFB Cat.7A S/FTP 1200 AWG22 B2ca
Cabling standards	ISO/IEC 11801
Category	7A
Characteristic impedance	100 ± 5 Ohm
Conductor category	Class 1 = solid
Conductor material	Copper, tinned
Core identification	Colour
Core insulation	Foam-Skin-PE
Coupling attenuation	≤ 85 dB
Diameter conductor	0.62 mm
Directive/Regulation	RoHS 2011/65/UE
Euro class	B2ca
Flame retardant	acc. to EN 60332-1
Halogen free	acc. to EN 60754-1/2

This datasheet was created automatically on 18-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

DATASHEET

INFRALAN® Cat.7A 1200 AWG22, S/FTP 4P CPR B2ca orange RAL 2003

Harmonised Standard	EN 50575
Installation standard	EN 50174
Insulation resistance (500V)	≥ 2000 MOhm/km
Loop resistance	143.4 Ohm/km
Low smoke	acc. to EN 61034
Material outer sheath	FRNC-B
Max. Freuqency	MHz MHz
NVP value	78 %
Operating capacity	43 pF/km
Operating temperature, fix	-20 – 60 °C
Operating temperature, flexible	-20 – 50 °C
Operating temperature, storage	-20 – 60 °C
PoE	acc. to IEEE802.3af PoE
Resistance unbalance	< 3 %
Screen over stranding	braiding
Screen over stranding element	Foil
Separation class acc. EN50174-2	D
Stranding element	Pairs
Test voltage DC, 1 min	1000 V
Transmission standards	IEEE 802.3 10Mbit bis 10Gbit
UV resistant	no

Available variants

ArtNr.	Bezeichnung	Colour outer sheath	Length	Number of cores	RAL colour	Type	Copper weight	Weight	Max. tractive force	Outer diameter approx.	Fire load
MK7100.1-CPR	INFRALAN® Cat.7A 1200 AWG22, S/FTP 4P CPR B2ca orange RAL 2003	orange	1.0 m	8	RAL 2003	simplex	3.62 kg/km	78 kg/km	100 N	8.4 mm	640 MJ/km
MK7100DX.500-CPR	INFRALAN® Cat.7A 1200 AWG22, S/FTP 2x4P CPR B2ca orange RAL 2003	orange	500.0 m	2x8	RAL 2003	duplex	7.24 kg/km	156 kg/km	100 N	8.4 x16.8 mm	1100 MJ/km

This datasheet was created automatically on 18-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

DATASHEET

INFRALAN® Cat.7A 1200 AWG22, S/FTP 4P CPR B2ca orange RAL 2003

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION