


DATASHEET

MTP®(F)-LC Trunk cable OM4 8 fibers Typ B LSZH erica-violet 10m

100 Gbit



General data

Application: Suitable for transmission links up to **100 Gigabit**

Construction: 1 multi-connector MTP® on one side,
4 LC-Duplex connector on the other side

LowLoss version: attenuation per Fanout max. 0,35dB

Matrix: 8 fibers

Assignment MTP 1-4 + 9-12

Furcation length: 50cm

Cable diameter multi-connector: 3mm

Cable diameter single-connector: 2mm

Colour: OM4 and OS2 acc. to colour code DIN VDE 0888

Technical properties

Cable Diameter	3.0 mm
Category	OM4
Coding	Crossed
Colour outer sheath	erica-violet
Connector connection 1	MTP®(F)
Connector connection 2	LC

This datasheet was created automatically on 21-09-2026 . Technical changes reserved.



DATASHEET

MTP®(F)-LC Trunk cable OM4 8 fibers Typ B LSZH erica-violet 10m

Crossed	Yes
Data rate	40G/ 100G/ 200G/ 400G
Fibre type	OM4 50/125
Flame retardant	Yes
Guide pins side A	False
Guide pins side B	False
Halogen free (according to EN 50267-2-3)	True
Material outer sheath	LSZH
Operating temperature	-20 - 70 °C
Storage Temperature	-20 - 70 °C
Wave length	850/1300 nm
With rodent protection	False

Available variants

ArtNr.	Bezeichnung	Halogen free (according to EN 60754-1/2)	Length	Number of connectors connection 1	Number of connectors connection 2	Number of fibres
MTPF08LCOM4-10	MTP®(F)-LC Trunk cable OM4 8 fibers Typ B LSZH erica-violet 10m	True	10.0 m	1 x MTP® (F)	8 x LC	8
MTPF08LCOM4-15	MTP®(F)-LC Trunk cable OM4 8 fibers Typ B LSZH erica-violet 15m	True	15.0 m	1 x MTP® (F)	8 x LC	8
MTPF08LCOM4-3	MTP®(F)-LC Trunk cable OM4 8 fibers Typ B LSZH erica-violet 3m	True	3.0 m	1 x MTP® (F)	8 x LC	8
MTPF08LCOM4-5	MTP®(F)-LC Trunk cable OM4 8 fibers Typ B LSZH erica-violet 5m	True	5.0 m	1 x MTP® (F)	8 x LC	8

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 21-09-2026 . Technical changes reserved.

