
DATASHEET

MTP®(F)-MTP®(F) Patch cable OM4 24 fibers Typ A LSZH erica-violet 5m



General data

Application: Server to Server- / Switch to Switch connection,
Suitable for transmission links up to **100 Gigabit**
Connector manufacturer: **US Conec**
Matrix: 12 Fibers
Singlemode variant always as APC version
Colour: OM5 lime green, OM4 erica-violet, OM3 aqua and OS2 yellow

Available lengths: 1m up to 100m

Note: In each MTP® transmission link, a type B (crossed) patch cable is required

Technical properties	
Cable Diameter	9.0 mm
Category	OM4
Coding	1:1
Colour outer sheath	erica-violet
Connector connection 1	MTP®(F)
Connector connection 2	MTP®(F)

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

DATASHEET

MTP®(F)-MTP®(F) Patch cable OM4 24 fibers Typ A LSZH erica-violet 5m

Crossed	No
Data rate	100G/ 400G/ 800G
Fibre type	OM4 50/125
Flame retardant	IEC 60332-1
Guide pins side A	False
Guide pins side B	False
Halogen free (according to EN 50267-2-3)	True
Material outer sheath	LSZH
Operating temperature	-20 – 70 °C
Storage Temperature	-20 – 70 °C
Wave length	850/1300 nm
With rodent protection	False

Available variants

ArtNr.	Bezeichnung	Halogen free (according to EN 60754-1/2)	Length	Number of connectors connection 1	Number of connectors connection 2	Number of fibres
MTPF24MTPFOM4-10-A	MTP®(F)-MTP®(F) Patch cable OM4 24 fibers Typ A LSZH erica-violet 10m	True	10.0 m	2 x MTP® (F)	2 x MTP® (F)	24
MTPF24MTPFOM4-5-A	MTP®(F)-MTP®(F) Patch cable OM4 24 fibers Typ A LSZH erica-violet 5m	True	5.0 m	2 x MTP® (F)	2 x MTP® (F)	24

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION