
DATASHEET

MTP®/APC(F)-MTP®/APC(F) Patch cable OS2 36 fibers Typ A LSZH yellow 15m



General data

Application: Server to Server- / Switch to Switch connection,
Suitable for transmission links up to **100 Gigabit**
Connector manufacturer: **US Conec**
Matrix: 12 Fibers
Singlemode variant always as APC version
Colour: OM5 lime green, OM4 erica-violet, OM3 aqua and OS2 yellow

Available lengths: 1m up to 100m

Note: In each MTP® transmission link, a type B (crossed) patch cable is required

MTP Singlemode connectors are in APC version

Technical properties	
Cable Diameter	9.0 mm
Category	OS2
Coding	1:1
Colour outer sheath	yellow

This datasheet was created automatically on 22-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

DATASHEET

MTP®/APC(F)-MTP®/APC(F) Patch cable OS2 36 fibers Typ A LSZH yellow 15m

Connector connection 1	MTP®/APC(F)
Connector connection 2	MTP®/APC(F)
Crossed	No
Data rate	100G/ 400G/ 800G
Fibre type	G657A1 9/125
Flame retardant	IEC 60332-1
Guide pins side A	False
Guide pins side B	False
Halogen free (according to EN 50267-2-3)	True
Material outer sheath	LSZH
Operating temperature	-20 – 70 °C
Storage Temperature	-20 – 70 °C
Wave length	1310/ 1550 nm
With rodent protection	False

Available variants

ArtNr.	Bezeichnung	Halogen free (according to EN 60754-1/2)	Length	Number of connectors connection 1	Number of connectors connection 2	Number of fibres
MTPF36MTPFOS2-10-A	MTP®/APC(F)-MTP®/APC(F) Patch cable OS2 36 fibers Typ A LSZH yellow 10m	True	10.0 m	3 x MTP®/APC(F)	3 x MTP®/APC(F)	36
MTPF36MTPFOS2-15-A	MTP®/APC(F)-MTP®/APC(F) Patch cable OS2 36 fibers Typ A LSZH yellow 15m	True	15.0 m	3 x MTP®/APC(F)	3 x MTP®/APC(F)	36
MTPF36MTPFOS2-5-A	MTP®/APC(F)-MTP®/APC(F) Patch cable OS2 36 fibers Typ A LSZH yellow 5m	True	5.0 m	3 x MTP®/APC(F)	3 x MTP®/APC(F)	36

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION