
# DATASHEET

## Duplex Patchcable LC-LC OM4 10m LSZH 1,2mm heathervi-olet



### General data

The 1.2 mm Duplex Jumper are characterized due to the small outer diameter. This is an advantage for the installers when they have limited space for cable management. The small outer diameter is also useful in projects with high density areas.

**Characteristics**

Space-saving installation due to the small outer diameter
Halogen free according to IEC-60754-2
Flame retardant according to IEC-60332-1
Low smoke according to IEC-61034
Connector in colour of category (aqua, erika-violet or blue)
LC connector in Compact design
EFB fiber connectors meet the quality classes
Grade B/2 according to IEC-61753-1 for Singlemode
Grade A/1 according to IEC-61753-122-2 (Draft) for Multimode
pre-coded
100% tested and with individuell measuring protocol

### Technical properties

| | |
|---|---|
| Anti-kink sleeve | put-on |

**This datasheet was created automatically on 01-11-2026 . Technical changes reserved.**

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

# DATASHEET

## Duplex Patchcable LC-LC OM4 10m LSZH 1,2mm heathervi-olet

| | |
|---|---|
| Bend optimized fiber | no |
| Cable structure | Duplex |
| Cable type | I-V(ZN) H |
| Cable Ø | 1.2 mm |
| Category | OM4 |
| Colour outer sheath | erica-violet |
| Fibre type | Multi mode 50/125 |
| Flame retardant | acc. to IEC 60332-1-2 |
| Halogen free | acc. to IEC 62821 |
| Insertion loss 850nm | ≤0,25 dB |
| Low smoke | acc. to IEC 61034 |
| Material outer sheath | LSZH |
| Min. Bending radius (Dynamic) | 20xOD mm |
| Min. Bending radius (Static) | 10xOD mm |
| Number of fibres | 2 |
| Operating Temperature | -20 – 60 °C |
| Packaging | EFB-Electronics poly bag (resealable) |
| Reinforcment | Aramid |
| Return loss 850nm | ≥35 dB |
| Scope of delivery | 1x Patchcable, 2x Duplex Clip, 1x Measurement Report, 1x Information Sheet |
| Storage Temperature | -20 – 70 °C |
| Type of connector connection 1 | LC |
| Type of connector connection 2 | LC |

**Available variants**

| ArtNr. | Bezeichnung | Length | Outer diameter sheath single fibre | Length tolerance |
|---|---|---|---|---|
| O0319.0,5-1.2 | Duplex Patchcable LC-LC OM4 0,5m LSZH 1,2mm heatherviolet | 0.5 m | 1.2 mm | ±5 % |
| O0319.1-1.2 | Duplex Patchcable LC-LC OM4 1m LSZH 1,2mm heatherviolet | 1.0 m | 1.2 mm | ±5 % |
| O0319.1,5-1.2 | Duplex Patchcable LC-LC OM4 1,5m LSZH 1,2mm heatherviolet | 1.5 m | 1.2 mm | ±5 % |
| O0319.10-1.2 | Duplex Patchcable LC-LC OM4 10m LSZH 1,2mm heatherviolet | 10.0 m | 1.2 mm | ±5 % |

**This datasheet was created automatically on 01-11-2026 . Technical changes reserved.**

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

# DATASHEET

## Duplex Patchcable LC-LC OM4 10m LSZH 1,2mm heathervi-olet

| | | | | |
|---|---|---|---|---|
| O0319.15-1.2 | Duplex Patchcable LC-LC OM4 15m LSZH 1,2mm heatherviolet | 15.0 m | 1.2 mm | ±5 % |
| O0319.2-1.2 | Duplex Patchcable LC-LC OM4 2m LSZH 1,2mm heatherviolet | 2.0 m | 1.2 mm | ±5 % |
| O0319.20-1.2 | Duplex Patchcable LC-LC OM4 20m LSZH 1,2mm heatherviolet | 20.0 m | 1.2 mm | ±5 % |
| O0319.25-1.2 | Duplex Patchcable LC-LC OM4 25m LSZH 1,2mm heatherviolet | 25.0 m | 1.2 mm | ±5 % |
| O0319.3-1.2 | Duplex Patchcable LC-LC OM4 3m LSZH 1,2mm heatherviolet | 3.0 m | 1.2 mm | ±5 % |
| O0319.5-1.2 | Duplex Patchcable LC-LC OM4 5m LSZH 1,2mm heatherviolet | 5.0 m | 1.2 mm | ±5 % |

**Note on Intended Use**

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.



EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION