

DATASHEET

Duplex Patchcable LC-LC OM5 0,5m LSZH 2mm limegreen



General data	
Technical properties	
Anti-kink sleeve	put-on
Bend optimized fiber	OM5 acc. to IEC60793-2-10 type A1a.4
Cable structure	Duplex
Cable type	I-V(ZN) H
Category	OM5
Colour outer sheath	lime green
Fibre type	Multi mode 50/125
Flame retardant	acc. to EN 50265-2-1
Low smoke	acc. to IEC 61034-1
Material outer sheath	LSZH
Max. Tension (long term)	160 N
Min. Bending radius (Dynamic)	20xOD
Min. Bending radius (Static)	10xOD
Number of fibres	2
Type of connector connection 1	LC
Type of connector connection 2	LC

Available variants		
ArtNr.	Bezeichnung	Length
00319.2,5OM5	Duplex Patchcable LC-LC OM5 0,5m LSZH 2mm limegreen	2.5 m

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

