

DATASHEET

R&M Duplex Patchcable E2000™ -LC OM4 20m LSZH 2mm heatherviolet Grade Bm



General data

Fiber jumper are well defined components in international standard of structured cabling ISO/IEC11801. Due to many different network protocols created in the last 25 years , also a wide range of connectors had been developed. Some of them are still important today: LC, SC, E2000®, MPO/MTP.

Fiber jumper (patchcord) are defined as shortest connection between passive interface and active deviceport, regarding structured cabling standard. Rating of performance, known as category, as well as performance of total transmission channel, known as link class, Similar descriptions for patchcords: Connection cable, drop cable, adapter cable, interconnecting cord, Jumper

Features of EFB fiber optic patch cables

Tension relief reinforced with aramid yarn

Halogen-free and flame-retardant sheath according to IEC-60754-2, IEC-60332-1 and IEC-61034

Technical properties

Anti-kink sleeve	put-on
Bend optimized fiber	no
Cable structure	Duplex
Cable type	I-V(ZN) H
Cable Ø	2 mm
Category	OM4
Colour outer sheath	erica-violet
Fibre type	Multimode 50/125
Flame retardant	acc. to IEC 60332-1
Halogen free	acc. to IEC 60754-2

This datasheet was created automatically on 21-09-2026 . Technical changes reserved.



DATASHEET

R&M Duplex Patchcable E2000™ -LC OM4 20m LSZH 2mm heatherviolet Grade Bm

Insertion loss 850nm	≤ 0,15 dB
Low smoke	acc. to IEC 61034-1
Material outer sheath	LSZH
Min. Bending radius (Dynamic)	50mm mm
Min. Bending radius (Static)	30mm mm
Number of fibres	2
Operating Temperature	-20 - 70 °C
Packaging	EFB-Electronics poly bag (resealable)
Reinforcement	Aramid
Return loss 850nm	≥35 dB
Scope of delivery	1x Patchcable, 2x Duplex Clip, 1x Measurement Report, 1x Information Sheet
Storage Temperature	-25 - 60 °C
Type of connector connection 1	E2000®
Type of connector connection 2	LC

Available variants

ArtNr.	Bezeichnung	Length	Length tolerance
00341.1	R&M Duplex Patchcable E2000™ -LC OM4 1m LSZH 2mm heatherviolet Grade Bm	1.0 m	±5 %
00341.10	R&M Duplex Patchcable E2000™ -LC OM4 10m LSZH 2mm heatherviolet Grade Bm	10.0 m	±5 %
00341.15	R&M Duplex Patchcable E2000™ -LC OM4 15m LSZH 2mm heatherviolet Grade Bm	15.0 m	±5 %
00341.2	R&M Duplex Patchcable E2000™ -LC OM4 2m LSZH 2mm heatherviolet Grade Bm	2.0 m	±5 %
00341.20	R&M Duplex Patchcable E2000™ -LC OM4 20m LSZH 2mm heatherviolet Grade Bm	20.0 m	±5 %
00341.3	R&M Duplex Patchcable E2000™ -LC OM4 3m LSZH 2mm heatherviolet Grade Bm	3.0 m	±5 %
00341.5	R&M Duplex Patchcable E2000™ -LC OM4 5m LSZH 2mm heatherviolet Grade Bm	5.0 m	±5 %
00341.7,5	R&M Duplex Patchcable E2000™ -LC OM4 7,5m LSZH 2mm heatherviolet Grade Bm	7.5 m	±5 %

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 21-09-2026 . Technical changes reserved.

