


DATASHEET

Fiber Pigtail ST OM3 -colored set 2m - 12 pieces



General data

The ST fiber pigtail set consists of 12 pigtails. The 12 pigtails are coloured according to colour code DIN VDE 0888 red, green, blue, yellow, white, grey, brown, violet, turquoise, black, orange and pink. The colour of the 900 μ jacket is equal to the colour of the 250 μ jacket. All 12 pigtails are packed in a polybag. Each connector is packed separately for an easy remove of each pigtail. Every PU contains an individual measuring protocol.

Technical properties

Anti-kink sleeve	put-on
Bend optimized fiber	no
Buffer	loose
Cable Conform to Standard	IEC60793-2
Category	OM3
Colour	DIN-Colorcode
Colour Code	VDE-0888
Connector Colour	silver
Connector Conform to Standard	IEC61754-2
Core type	Semi tight
Fibre type	Multi mode 50/125
Insertion loss 850nm	< 0.3 dB

This datasheet was created automatically on 22-09-2026 . Technical changes reserved.

DATASHEET

Fiber Pigtail ST OM3 -colored set 2m - 12 pieces

Length	2.0 m
Material outer sheath	LSZH
Max. Tension (long term)	3 N
Measurement protocol available	Yes
Minimaler Biegeradius Dynamic	20xOD
Mion. Bending Radius Static	10xOD
Operating temperature	-20 - 70 °C
Outer diameter	0.9 mm
Packaging	Polybag
Quality class Multimode	A/1 according to IEC-61753-222-2
Scope of delivery	1 Pigtail
Type	Conductor pigtail
Type of connector	ST

Available variants

ArtNr.	Bezeichnung	Unique
03305.2	Fiber Pigtail ST OM3 -colored set 2m - 12 pieces	Unique

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 22-09-2026 . Technical changes reserved.

