


DATASHEET

Fiber Pigtail ST OM1 -Blue 2m - 1 piece



General data

The ST fiber pigtail has a primary coating (900μ) in the colour of the respective category (see table). The colour of the primary coating is equal to the colour of the secondary coating. Every PU contains an individual measuring protocol.

Technical properties

Anti-kink sleeve	put-on
Bend optimized fiber	no
Buffer	loose
Cable Conform to Standard	IEC60793-2
Category	OM1
Colour	blue
Colour Code	one colour
Connector Colour	silver
Connector Conform to Standard	IEC61754-2
Core type	Semi tight
Fibre type	Multimode 62,5/125
Insertion loss 850nm	< 0.3 dB
Length	2.0 m

This datasheet was created automatically on 20-09-2026 . Technical changes reserved.



DATASHEET

Fiber Pigtail ST OM1 -Blue 2m - 1 piece

Material outer sheath	LSZH
Max. Tension (long term)	3 N
Measurement protocol available	Yes
Minimaler Biegeradius Dynamic	20xOD
Mion. Bending Radius Static	10xOD
Operating temperature	-20 - 70 °C
Outer diameter	0.9 mm
Packaging	Polybag
Quality class Multimode	A/1 according to IEC-61753-222-2
Scope of delivery	1 Pigtail
Type	Conductor pigtail
Type of connector	ST

Available variants

ArtNr.	Bezeichnung	Unique
03313.2	Fiber Pigtail ST OM1 -Blue 2m - 1 piece	Unique

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 20-09-2026 . Technical changes reserved.

