
DATASHEET

Fiber Pigtail SC OM3 -Aqua 2m - 1 piece



General data

The SC OM3 compact tube fibre pigtail from EFB-Elektronik is designed for professional fibre optic splice connections in multimode fibre optic networks. The version as a 2.0 m long single pigtail is intended for standard-compliant use in the installation environment.

• Multimode 50/125 in OM3 category – Supports use in professional fibre optic splice connections with clear multimode mapping.
• SC connector according to IEC61754-4 – Ensures a standard-compliant interface and clear identification through the aqua-coloured design.
• 2.0 m compact tube with 0.9 mm outer diameter, loose buffer and attached strain-relief boot – Facilitates processing in the splice area and protects the fibre transition.

Technically, it is a wire pigtail with an outer diameter of 0.9 mm and a loose buffer. The multimode version in the OM3 category is specified according to IEC-61753-222-2 in quality class A/1. The SC connector corresponds to IEC61754-4 and is designed in Aqua. The monochrome marking supports the assignment. An attached strain-relief boot grommet is provided and a test report is available.

Technical details
• Type: fibre pigtail
• Fibre construction: tight-buffered fibre
• Connector type: SC

This datasheet was created automatically on 25-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

DATASHEET

Fiber Pigtail SC OM3 -Aqua 2m - 1 piece

- Fibre type: Multimode 50/125
- Category: OM3
- Multimode quality class: A/1 according to IEC-61753-222-2
- Length: 2.0 m
- Outer diameter: 0.9 mm
- Buffer: loose
- Colour: aqua
- Colour code: solid colour
- Connector colour: aqua
- Connector standard: IEC61754-4
- Cable standard: IEC60793-2
- With fitted strain-relief boot
- Test report available
- Scope of delivery: 1 pigtail

Technical properties	
Anti-kink sleeve	put-on
Bend optimized fiber	no
Buffer	loose
Cable Conform to Standard	IEC60793-2
Category	OM3
Colour	aqua
Colour Code	one colour
Connector Colour	aqua
Connector Conform to Standard	IEC61754-4
Core type	Semi tight
Fibre type	Multi mode 50/125
Insertion loss 850nm	< 0.3 dB
Length	2.0 m
Material outer sheath	LSZH
Max. Tension (long term)	3 N
Measurement protocol available	Yes
Minimaler Biegeradius Dynamic	20xOD
Mion. Bending Radius Static	10xOD
Operating temperature	-20 – 70 °C
Outer diameter	0.9 mm
Packaging	Polybag
Quality class Multimode	A/1 according to IEC-61753-222-2
Scope of delivery	1 Pigtail
Type	Conductor pigtail

This datasheet was created automatically on 25-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

DATASHEET

Fiber Pigtail SC OM3 -Aqua 2m - 1 piece

Type of connector	SC

Available variants

ArtNr.	Bezeichnung	Unique
O3623.2	Fiber Pigtail SC OM3 -Aqua 2m - 1 piece	Unique

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 25-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION