

DATASHEET

U-DQ(ZN) BH 4G 50/125µm SC - SC OM4, 1 Meter LSZH black CPR-B2CA



General data

Characteristics and advantages of Trunk cables:

- 2 up to 48 fibers per cable (CPR class B2ca)
- Pre-assembled, polished and factory-tested
- Both-sided assembled with stepped plug whips
- Ready to use, no need for expensive splice- and measuring equipment
- With Premium or Standard cable divider at customers choice
- Attenuation protocol for each assembled connector included in delivery
- All possible combinations of connectors like LC and SC
- Identification with cable markers
- Delivery depending on length and type: one way drum or cable ring

Technical properties

Category	OM4
Coding	1:1
Colour outer sheath	black
Connector connection 1	SC
Connector connection 2	SC
Crossed	No
Fibre type	OM4 50/125
Flame retardant	nach IEC/EN 60332-3-24
Material outer sheath	LSZH
Operating temperature	-40 - 80 °C
Storage Temperature	-40 - 80 °C
With rodent protection	True

Available variants

ArtNr.	Bezeichnung	Cable type connector connection 2	Length Number of connectors connection 1	Number of connectors connection 2	Number of fibres
--------	-------------	---	---	---	---------------------

This datasheet was created automatically on 19-09-2026 . Technical changes reserved.



DATASHEET

U-DQ(ZN) BH 4G 50/125µm SC - SC OM4, 1 Meter LSZH black CPR-B2CA

O8301.1OM4-B2	U-DQ(ZN) BH 4G 50/125µm SC - SC OM4, 1 Meter LSZH black CPR-B2CA	Universal cable	1.0 m	4	4	4
O8341.1OM4-B2	U-DQ(ZN) BH 12G 50/125µm SC - SC OM4, 1 Meter LSZH black CPR-B2CA	Universal cable	1.0 m	12	12	12

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 19-09-2026 . Technical changes reserved.

