


DATASHEET

Trunk cable U-DQ(ZN)BH OS2 4E (1x4) SC-SC,10m Dca LSZH



General data

EFB-Elektronik sets standards in high quality

For many years, EFB-Elektronik has been offering individual fiber optic assemblies from its own production for insertion into cable ducts and shafts. Now there is also a standard line, which is kept in stock. These are pre-assembled trunk cables with SC connectors in the OS2, OM3 and OM4 categories. The stocked lengths can be found in the overview below.

Advantages:

Fast delivery: standard lengths up to 200 m in standard quantities available from stock

Reduction of installation costs: No splicing and assembly equipment required

Reduced installation time: cable ready for direct installation

Traceable quality: cable with serial number and measurement protocol

Performance features:

4, 8 or 12 fibers per cable

Fibre class OS2, OM3 or OM4

This datasheet was created automatically on 15-09-2026 . Technical changes reserved.



DATASHEET

Trunk cable U-DQ(ZN)BH OS2 4E (1x4) SC-SC,10m Dca LSZH

Factory production, polishing and function test

Double-sided assembled stepped cable whips (longest length 1 m)

Identification of the remote individual cables with cable markers (numbers)

Serial number on the cable

Attenuation protocol for each individual fiber is provided

Delivery on both sides with fabric hose as drawing-in tube

Delivery up to 40 m in polybag, from 50 m on disposable drum

Raw cable: CPR-Class Dca

Length of the draw-in tube of 130cm, diameter: 4 fiber approx. 10mm, 8 fiber approx. 15mm, 12 fiber approx. 20mm

Technical properties	
Anti-kink sleeve	put-on
Bend optimized fiber	no
Cable structure	Multifiber
Cable type	U-DQ (ZN) BH
Cable Ø	5.8 mm
Category	OS2 G652D
Colour outer sheath	black
Dimension Cable divider	11.5 x 72 mm
Fibre type	Single mode 9/125
Flame retardant	Yes
Insertion loss 1310nm	< 1.5 dB
Material outer sheath	LSZH
Max. Tension (long term)	300 N
Min. Bending radius (Dynamic)	>20xOD mm
Min. Bending radius (Static)	>10xOD mm
Number of fibres	4
Operating Temperature	-40 - 70 °C
Packaging	Drum
Scope of delivery	Cable, measurement protocol, GPSR instruction leaflet, insertion aid, coil
Storage Temperature	-40 - 70 °C
Type of connector connection 1	SC
Type of connector connection 2	SC

Available variants

This datasheet was created automatically on 15-09-2026 . Technical changes reserved.



DATASHEET

Trunk cable U-DQ(ZN)BH OS2 4E (1x4) SC-SC,10m Dca LSZH

ArtNr.	Bezeichnung	Length	Outer diameter sheath single fibre	Length tolerance
O8301S100S2	Trunk cable U-DQ(ZN)BH OS2 4E (1x4) SC-SC,10m Dca LSZH	10 m	2 mm	±5 %
O8301S120OS2	Trunk cable U-DQ(ZN)BH OS2 4E (1x4) SC-SC,120m Dca LSZH	120 m	2 mm	±5 %
O8301S140OS2	Trunk cable U-DQ(ZN)BH OS2 4E (1x4) SC-SC,140m Dca LSZH	140 m	2 mm	±5 %
O8301S150OS2	Trunk cable U-DQ(ZN)BH OS2 4E (1x4) SC-SC,150m Dca LSZH	150 m	2 mm	±5 %
O8301S160OS2	Trunk cable U-DQ(ZN)BH OS2 4E (1x4) SC-SC,160m Dca LSZH	160 m	2 mm	±5 %
O8301S170OS2	Trunk cable U-DQ(ZN)BH OS2 4E (1x4) SC-SC,170m Dca LSZH	170 m	2 mm	±5 %
O8301S180OS2	Trunk cable U-DQ(ZN)BH OS2 4E (1x4) SC-SC,180m Dca LSZH	180 m	2 mm	±5 %
O8301S190OS2	Trunk cable U-DQ(ZN)BH OS2 4E (1x4) SC-SC,190m Dca LSZH	190 m	2 mm	±5 %
O8301S200S2	Trunk cable U-DQ(ZN)BH OS2 4E (1x4) SC-SC,20m Dca LSZH	20 m	2 mm	±5 %
O8301S700S2	Trunk cable U-DQ(ZN)BH OS2 4E (1x4) SC-SC,70m Dca LSZH	70 m	2 mm	±5 %
O8301S900S2	Trunk cable U-DQ(ZN)BH OS2 4E (1x4) SC-SC,90m Dca LSZH	90 m	2 mm	±5 %

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 15-09-2026 . Technical changes reserved.

