


DATASHEET

Trunk cable U-DQ(ZN)BH OM3 4G (1x4) SC-SC,80m Dca LSZH



General data

EFB-Elektronik sets standards in high quality

For many years, EFB-Elektronik has been offering individual fiber optic assemblies from its own production for insertion into cable ducts and shafts. Now there is also a standard line, which is kept in stock. These are pre-assembled trunk cables with SC connectors in the OS2, OM3 and OM4 categories. The stocked lengths can be found in the overview below.

Advantages:

Fast delivery: standard lengths up to 200 m in standard quantities available from stock

Reduction of installation costs: No splicing and assembly equipment required

Reduced installation time: cable ready for direct installation

Traceable quality: cable with serial number and measurement protocol

Performance features:

4, 8 or 12 fibers per cable

Fibre class OS2, OM3 or OM4

This datasheet was created automatically on 11-09-2026 . Technical changes reserved.



DATASHEET

Trunk cable U-DQ(ZN)BH OM3 4G (1x4) SC-SC,80m Dca LSZH

Factory production, polishing and function test

Double-sided assembled stepped cable whips (longest length 1 m)

Identification of the remote individual cables with cable markers (numbers)

Serial number on the cable

Attenuation protocol for each individual fiber is provided

Delivery on both sides with fabric hose as drawing-in tube

Delivery up to 40 m in polybag, from 50 m on disposable drum

Raw cable: CPR-Class Dca

Length of the draw-in tube of 130cm, diameter: 4 fiber approx. 10mm, 8 fiber approx. 15mm, 12 fiber approx. 20mm

Technical properties	
Anti-kink sleeve	put-on
Bend optimized fiber	no
Cable structure	Multifiber
Cable type	U-DQ (ZN) BH
Cable Ø	5.8 mm
Category	OM3
Colour outer sheath	black
Dimension Cable divider	11.5 x 50 mm
Fibre type	Multi mode 50/125
Flame retardant	Yes
Insertion loss 850nm	< 3,5 dB
Material outer sheath	LSZH
Max. Tension (long term)	300 N
Min. Bending radius (Dynamic)	20xOD mm
Min. Bending radius (Static)	10xOD mm
Number of fibres	4
Operating Temperature	-40 - 70 °C
Packaging	Polybag
Scope of delivery	Cable, measurement protocol, GPSR instruction leaflet, insertion aid
Storage Temperature	-40 - 70 °C
Type of connector connection 1	SC
Type of connector connection 2	SC

Available variants

This datasheet was created automatically on 11-09-2026 . Technical changes reserved.



DATASHEET

Trunk cable U-DQ(ZN)BH OM3 4G (1x4) SC-SC,80m Dca LSZH

ArtNr.	Bezeichnung	Length	Outer diameter sheath single fibre	Length tolerance
O8301S100M3	Trunk cable U-DQ(ZN)BH OM3 4G (1x4) SC-SC,10m Dca LSZH	10 m	2 mm	±5 %
O8301S1100M3	Trunk cable U-DQ(ZN)BH OM3 4G (1x4) SC-SC,110m Dca LSZH	110 m	2 mm	±5 %
O8301S1300M3	Trunk cable U-DQ(ZN)BH OM3 4G (1x4) SC-SC,130m Dca LSZH	130 m	2 mm	±5 %
O8301S1400M3	Trunk cable U-DQ(ZN)BH OM3 4G (1x4) SC-SC,140m Dca LSZH	140 m	2 mm	±5 %
O8301S1500M3	Trunk cable U-DQ(ZN)BH OM3 4G (1x4) SC-SC,150m Dca LSZH	150 m	2 mm	±5 %
O8301S1600M3	Trunk cable U-DQ(ZN)BH OM3 4G (1x4) SC-SC,160m Dca LSZH	160 m	2 mm	±5 %
O8301S1700M3	Trunk cable U-DQ(ZN)BH OM3 4G (1x4) SC-SC,170m Dca LSZH	170 m	2 mm	±5 %
O8301S1800M3	Trunk cable U-DQ(ZN)BH OM3 4G (1x4) SC-SC,180m Dca LSZH	180 m	2 mm	±5 %
O8301S1900M3	Trunk cable U-DQ(ZN)BH OM3 4G (1x4) SC-SC,190m Dca LSZH	190 m	2 mm	±5 %
O8301S2000M3	Trunk cable U-DQ(ZN)BH OM3 4G (1x4) SC-SC,200m Dca LSZH	200 m	2 mm	±5 %
O8301S200M3	Trunk cable U-DQ(ZN)BH OM3 4G (1x4) SC-SC,20m Dca LSZH	20 m	2 mm	±5 %
O8301S300M3	Trunk cable U-DQ(ZN)BH OM3 4G (1x4) SC-SC,30m Dca LSZH	30 m	2 mm	±5 %
O8301S400M3	Trunk cable U-DQ(ZN)BH OM3 4G (1x4) SC-SC,40m Dca LSZH	40 m	2 mm	±5 %
O8301S500M3	Trunk cable U-DQ(ZN)BH OM3 4G (1x4) SC-SC,50m Dca LSZH	50 m	2 mm	±5 %
O8301S600M3	Trunk cable U-DQ(ZN)BH OM3 4G (1x4) SC-SC,60m Dca LSZH	60 m	2 mm	±5 %
O8301S700M3	Trunk cable U-DQ(ZN)BH OM3 4G (1x4) SC-SC,70m Dca LSZH	70 m	2 mm	±5 %
O8301S800M3	Trunk cable U-DQ(ZN)BH OM3 4G (1x4) SC-SC,80m Dca LSZH	80 m	2 mm	±5 %
O8301S900M3	Trunk cable U-DQ(ZN)BH OM3 4G (1x4) SC-SC,90m Dca LSZH	90 m	2 mm	±5 %

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and

This datasheet was created automatically on 11-09-2026 . Technical changes reserved.



DATASHEET

Trunk cable U-DQ(ZN)BH OM3 4G (1x4) SC-SC,80m Dca
LSZH

regulatory requirements.

This datasheet was created automatically on 11-09-2026 . Technical changes reserved.

