
DATASHEET

Trunk cable U-DQ(ZN)BH OM4 4G (1x4) LC-LC,160m Dca LSZH



General data

EFB-Elektronik sets standards in high quality

For many years, EFB-Elektronik has been offering individual fiber optic assemblies from its own production for insertion into cable ducts and shafts. Now there is also a standard line, which is kept in stock. These are pre-assembled trunk cables with LC connectors in the OS2, OM3 and OM4 categories. The stocked lengths can be found in the overview below.

Advantages:
Fast delivery: standard lengths up to 200 m in standard quantities available from stock
Reduction of installation costs: No splicing and assembly equipment required
Reduced installation time: cable ready for direct installation

This datasheet was created automatically on 30-10-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

DATASHEET

Trunk cable U-DQ(ZN)BH OM4 4G (1x4) LC-LC,160m Dca LSZH

Traceable quality: cable with serial number and measurement protocol

Performance features:
4, 8 or 12 fibers per cable
Fibre class OS2, OM3 or OM4
Factory production, polishing and function test
Double-sided assembled stepped cable whips (longest length 1 m)
Identification of the remote individual cables with cable markers (numbers)
Serial number on the cable
Attenuation protocol for each individual fiber is provided
Delivery on both sides with fabric hose as drawing-in tube
Delivery up to 40 m in polybag, from 50 m on disposable drum
Raw cable: CPR-Class Dca
Length of the draw-in tube of 130cm, diameter: 4 fiber approx. 10mm, 8 fiber approx. 15mm, 12 fiber approx. 20mm

Technical properties	
Anti-kink sleeve	put-on
Bend optimized fiber	no
Cable structure	Multifiber
Cable type	U-DQ (ZN) BH
Cable Ø	5.8 mm
Category	OM4
Colour outer sheath	black
Dimension Cable divider	11.5 x 112 mm
Fibre type	Multi mode 50/125
Flame retardant	Yes
Insertion loss 850nm	< 3,5 dB
Material outer sheath	LSZH
Max. Tension (long term)	300 N
Min. Bending radius (Dynamic)	20xOD mm
Min. Bending radius (Static)	10xOD mm
Number of fibres	4
Operating Temperature	-40 – 70 °C
Packaging	Polybag
Scope of delivery	Cable, measurement protocol, GPSR instruction leaflet, insertion aid
Storage Temperature	-40 – 70 °C
Type of connector connection 1	LC
Type of connector connection 2	LC

This datasheet was created automatically on 30-10-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

DATASHEET

Trunk cable U-DQ(ZN)BH OM4 4G (1x4) LC-LC,160m Dca LSZH

Available variants

ArtNr.	Bezeichnung	Length	Outer diameter sheath single fibre	Length tolerance
O8303S100OM4	Trunk cable U-DQ(ZN)BH OM4 4G (1x4) LC-LC,100m Dca LSZH	100 m	2 mm	±5 %
O8303S10OM4	Trunk cable U-DQ(ZN)BH OM4 4G (1x4) LC-LC,10m Dca LSZH	10 m	2 mm	±5 %
O8303S110OM4	Trunk cable U-DQ(ZN)BH OM4 4G (1x4) LC-LC,110m Dca LSZH	110 m	2 mm	±5 %
O8303S120OM4	Trunk cable U-DQ(ZN)BH OM4 4G (1x4) LC-LC,120m Dca LSZH	120 m	2 mm	±5 %
O8303S130OM4	Trunk cable U-DQ(ZN)BH OM4 4G (1x4) LC-LC,130m Dca LSZH	130 m	2 mm	±5 %
O8303S140OM4	Trunk cable U-DQ(ZN)BH OM4 4G (1x4) LC-LC,140m Dca LSZH	140 m	2 mm	±5 %
O8303S150OM4	Trunk cable U-DQ(ZN)BH OM4 4G (1x4) LC-LC,150m Dca LSZH	150 m	2 mm	±5 %
O8303S160OM4	Trunk cable U-DQ(ZN)BH OM4 4G (1x4) LC-LC,160m Dca LSZH	160 m	2 mm	±5 %
O8303S170OM4	Trunk cable U-DQ(ZN)BH OM4 4G (1x4) LC-LC,170m Dca LSZH	170 m	2 mm	±5 %
O8303S180OM4	Trunk cable U-DQ(ZN)BH OM4 4G (1x4) LC-LC,180m Dca LSZH	180 m	2 mm	±5 %
O8303S190OM4	Trunk cable U-DQ(ZN)BH OM4 4G (1x4) LC-LC,190m Dca LSZH	190 m	2 mm	±5 %
O8303S200OM4	Trunk cable U-DQ(ZN)BH OM4 4G (1x4) LC-LC,200m Dca LSZH	200 m	2 mm	±5 %
O8303S20OM4	Trunk cable U-DQ(ZN)BH OM4 4G (1x4) LC-LC,20m Dca LSZH	20 m	2 mm	±5 %
O8303S30OM4	Trunk cable U-DQ(ZN)BH OM4 4G (1x4) LC-LC,30m Dca LSZH	30 m	2 mm	±5 %
O8303S40OM4	Trunk cable U-DQ(ZN)BH OM4 4G (1x4) LC-LC,40m Dca LSZH	40 m	2 mm	±5 %
O8303S50OM4	Trunk cable U-DQ(ZN)BH OM4 4G (1x4) LC-LC,50m Dca LSZH	50 m	2 mm	±5 %
O8303S60OM4	Trunk cable U-DQ(ZN)BH OM4 4G (1x4) LC-LC,60m Dca LSZH	60 m	2 mm	±5 %
O8303S70OM4	Trunk cable U-DQ(ZN)BH OM4 4G (1x4) LC-LC,70m Dca LSZH	70 m	2 mm	±5 %

This datasheet was created automatically on 30-10-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

DATASHEET

Trunk cable U-DQ(ZN)BH OM4 4G (1x4) LC-LC,160m Dca LSZH

O8303S80OM4	Trunk cable U-DQ(ZN)BH OM4 4G (1x4) LC-LC,80m Dca LSZH	80 m	2 mm	±5 %
O8303S90OM4	Trunk cable U-DQ(ZN)BH OM4 4G (1x4) LC-LC,90m Dca LSZH	90 m	2 mm	±5 %

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION