


DATASHEET

Trunk cable U-DQ(ZN)BH OM4 12G (1x12) SC-SC,120m
Dca LSZH



General data

EFB-Elektronik sets standards in high quality

For many years, EFB-Elektronik has been offering individual fiber optic assemblies from its own production for insertion into cable ducts and shafts. Now there is also a standard line, which is kept in stock. These are pre-assembled trunk cables with SC connectors in the OS2, OM3 and OM4 categories. The stocked lengths can be found in the overview below.

Advantages:

Fast delivery: standard lengths up to 200 m in standard quantities available from stock

Reduction of installation costs: No splicing and assembly equipment required

Reduced installation time: cable ready for direct installation

This datasheet was created automatically on 04-10-2026 . Technical changes reserved.

DATASHEET

Trunk cable U-DQ(ZN)BH OM4 12G (1x12) SC-SC,120m Dca LSZH

Traceable quality: cable with serial number and measurement protocol

Performance features:

4, 8 or 12 fibers per cable

Fibre class OS2, OM3 or OM4

Factory production, polishing and function test

Double-sided assembled stepped cable whips (longest length 1 m)

Identification of the remote individual cables with cable markers (numbers)

Serial number on the cable

Attenuation protocol for each individual fiber is provided

Delivery on both sides with fabric hose as drawing-in tube

Delivery up to 40 m in polybag, from 50 m on disposable drum

Raw cable: CPR-Class Dca

Length of the draw-in tube of 130cm, diameter: 4 fiber approx. 10mm, 8 fiber approx. 15mm, 12 fiber approx. 20mm

Technical properties

Anti-kink sleeve	put-on
Bend optimized fiber	no
Cable structure	Multifiber
Cable type	U-DQ (ZN) BH
Cable Ø	5.8 mm
Category	OM4
Colour outer sheath	black
Dimension Cable divider	11.5 x 292 mm
Fibre type	Multi mode 50/125
Flame retardant	Yes
Insertion loss 850nm	< 3,5 dB
Material outer sheath	LSZH
Max. Tension (long term)	300 N
Min. Bending radius (Dynamic)	20xOD mm
Min. Bending radius (Static)	10xOD mm
Number of fibres	12
Operating Temperature	-40 - 70 °C
Packaging	Polybag
Scope of delivery	Cable, measurement protocol, GPSR instruction leaflet, insertion aid
Storage Temperature	-40 - 70 °C
Type of connector connection 1	SC
Type of connector connection 2	SC

This datasheet was created automatically on 04-10-2026 . Technical changes reserved.



DATASHEET

Trunk cable U-DQ(ZN)BH OM4 12G (1x12) SC-SC,120m Dca LSZH

Available variants

ArtNr.	Bezeichnung	Length	Outer diameter sheath single fibre	Length tolerance
08341S1000M4	Trunk cable U-DQ(ZN)BH OM4 12G (1x12) SC-SC,100m Dca LSZH	100 m	2 mm	±5 %
08341S100M4	Trunk cable U-DQ(ZN)BH OM4 12G (1x12) SC-SC,10m Dca LSZH	10 m	2 mm	±5 %
08341S1100M4	Trunk cable U-DQ(ZN)BH OM4 12G (1x12) SC-SC,110m Dca LSZH	110 m	2 mm	±5 %
08341S1200M4	Trunk cable U-DQ(ZN)BH OM4 12G (1x12) SC-SC,120m Dca LSZH	120 m	2 mm	±5 %
08341S1300M4	Trunk cable U-DQ(ZN)BH OM4 12G (1x12) SC-SC,130m Dca LSZH	130 m	2 mm	±5 %
08341S1400M4	Trunk cable U-DQ(ZN)BH OM4 12G (1x12) SC-SC,140m Dca LSZH	140 m	2 mm	±5 %
08341S1500M4	Trunk cable U-DQ(ZN)BH OM4 12G (1x12) SC-SC,150m Dca LSZH	150 m	2 mm	±5 %
08341S1600M4	Trunk cable U-DQ(ZN)BH OM4 12G (1x12) SC-SC,160m Dca LSZH	160 m	2 mm	±5 %
08341S1700M4	Trunk cable U-DQ(ZN)BH OM4 12G (1x12) SC-SC,170m Dca LSZH	170 m	2 mm	±5 %
08341S1800M4	Trunk cable U-DQ(ZN)BH OM4 12G (1x12) SC-SC,180m Dca LSZH	180 m	2 mm	±5 %
08341S1900M4	Trunk cable U-DQ(ZN)BH OM4 12G (1x12) SC-SC,190m Dca LSZH	190 m	2 mm	±5 %
08341S2000M4	Trunk cable U-DQ(ZN)BH OM4 12G (1x12) SC-SC,200m Dca LSZH	200 m	2 mm	±5 %
08341S200M4	Trunk cable U-DQ(ZN)BH OM4 12G (1x12) SC-SC,20m Dca LSZH	20 m	2 mm	±5 %
08341S300M4	Trunk cable U-DQ(ZN)BH OM4 12G (1x12) SC-SC,30m Dca LSZH	30 m	2 mm	±5 %
08341S400M4	Trunk cable U-DQ(ZN)BH OM4 12G (1x12) SC-SC,40m Dca LSZH	40 m	2 mm	±5 %
08341S500M4	Trunk cable U-DQ(ZN)BH OM4 12G (1x12) SC-SC,50m Dca LSZH	50 m	2 mm	±5 %
08341S600M4	Trunk cable U-DQ(ZN)BH OM4 12G (1x12) SC-SC,60m Dca LSZH	60 m	2 mm	±5 %
08341S700M4	Trunk cable U-DQ(ZN)BH OM4 12G (1x12) SC-SC,70m Dca LSZH	70 m	2 mm	±5 %

This datasheet was created automatically on 04-10-2026 . Technical changes reserved.



DATASHEET

Trunk cable U-DQ(ZN)BH OM4 12G (1x12) SC-SC,120m Dca LSZH

O8341S800M4	Trunk cable U-DQ(ZN)BH OM4 12G (1x12) SC-SC,80m Dca LSZH	80 m	2 mm	±5 %
O8341S900M4	Trunk cable U-DQ(ZN)BH OM4 12G (1x12) SC-SC,90m Dca LSZH	90 m	2 mm	±5 %

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 04-10-2026 . Technical changes reserved.

