



DATASHEET


Trunk cable U-DQ(ZN)BH OM4 12G (1x12) SC-SC,50m Dca LSZH











General data

EFB-Elektronik sets standards in high quality

For many years, EFB-Elektronik has been offering individual fiber optic assemblies from its own production for insertion into cable ducts and shafts. Now there is also a standard line, which is kept in stock. These are pre-assembled trunk cables with SC connectors in the OS2, OM3 and OM4 categories. The stocked lengths can be found in the overview below.

Advantages:
Fast delivery: standard lengths up to 200 m in standard quantities available from stock
Reduction of installation costs: No splicing and assembly equipment required
Reduced installation time: cable ready for direct installation
Traceable quality: cable with serial number and measurement protocol

Performance features:
4, 8 or 12 fibers per cable
Fibre class OS2, OM3 or OM4

This datasheet was created automatically on 19-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

DATASHEET

Trunk cable U-DQ(ZN)BH OM4 12G (1x12) SC-SC,50m Dca LSZH

Factory production, polishing and function test
Double-sided assembled stepped cable whips (longest length 1 m)
Identification of the remote individual cables with cable markers (numbers)
Serial number on the cable
Attenuation protocol for each individual fiber is provided
Delivery on both sides with fabric hose as drawing-in tube
Delivery up to 40 m in polybag, from 50 m on disposable drum
Raw cable: CPR-Class Dca
Length of the draw-in tube of 130cm, diameter: 4 fiber approx. 10mm, 8 fiber approx. 15mm, 12 fiber approx. 20mm

Technical properties	
Anti-kink sleeve	put-on
Bend optimized fiber	no
Cable structure	Multifiber
Cable type	U-DQ (ZN) BH
Cable Ø	5.8 mm
Category	OM4
Colour outer sheath	black
Dimension Cable divider	11.5 x 292 mm
Fibre type	Multi mode 50/125
Flame retardant	Yes
Insertion loss 850nm	< 3,5 dB
Material outer sheath	LSZH
Max. Tension (long term)	300 N
Min. Bending radius (Dynamic)	>20xOD mm
Min. Bending radius (Static)	>10xOD mm
Number of fibres	12
Operating Temperature	-40 – 70 °C
Packaging	Polybag
Scope of delivery	Cable, measurement protocol, GPSR instruction leaflet, insertion aid
Storage Temperature	-40 – 70 °C
Type of connector connection 1	SC
Type of connector connection 2	SC

Available variants

This datasheet was created automatically on 19-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

DATASHEET

Trunk cable U-DQ(ZN)BH OM4 12G (1x12) SC-SC,50m Dca LSZH

ArtNr.	Bezeichnung	Length	Outer diameter sheath single fibre	Length tolerance
O8341S100OM4	Trunk cable U-DQ(ZN)BH OM4 12G (1x12) SC-SC,100m Dca LSZH	100 m	2 mm	±5 %
O8341S10OM4	Trunk cable U-DQ(ZN)BH OM4 12G (1x12) SC-SC,10m Dca LSZH	10 m	2 mm	±5 %
O8341S110OM4	Trunk cable U-DQ(ZN)BH OM4 12G (1x12) SC-SC,110m Dca LSZH	110 m	2 mm	±5 %
O8341S120OM4	Trunk cable U-DQ(ZN)BH OM4 12G (1x12) SC-SC,120m Dca LSZH	120 m	2 mm	±5 %
O8341S130OM4	Trunk cable U-DQ(ZN)BH OM4 12G (1x12) SC-SC,130m Dca LSZH	130 m	2 mm	±5 %
O8341S140OM4	Trunk cable U-DQ(ZN)BH OM4 12G (1x12) SC-SC,140m Dca LSZH	140 m	2 mm	±5 %
O8341S150OM4	Trunk cable U-DQ(ZN)BH OM4 12G (1x12) SC-SC,150m Dca LSZH	150 m	2 mm	±5 %
O8341S160OM4	Trunk cable U-DQ(ZN)BH OM4 12G (1x12) SC-SC,160m Dca LSZH	160 m	2 mm	±5 %
O8341S170OM4	Trunk cable U-DQ(ZN)BH OM4 12G (1x12) SC-SC,170m Dca LSZH	170 m	2 mm	±5 %
O8341S180OM4	Trunk cable U-DQ(ZN)BH OM4 12G (1x12) SC-SC,180m Dca LSZH	180 m	2 mm	±5 %
O8341S190OM4	Trunk cable U-DQ(ZN)BH OM4 12G (1x12) SC-SC,190m Dca LSZH	190 m	2 mm	±5 %
O8341S200OM4	Trunk cable U-DQ(ZN)BH OM4 12G (1x12) SC-SC,200m Dca LSZH	200 m	2 mm	±5 %
O8341S20OM4	Trunk cable U-DQ(ZN)BH OM4 12G (1x12) SC-SC,20m Dca LSZH	20 m	2 mm	±5 %
O8341S30OM4	Trunk cable U-DQ(ZN)BH OM4 12G (1x12) SC-SC,30m Dca LSZH	30 m	2 mm	±5 %
O8341S40OM4	Trunk cable U-DQ(ZN)BH OM4 12G (1x12) SC-SC,40m Dca LSZH	40 m	2 mm	±5 %
O8341S50OM4	Trunk cable U-DQ(ZN)BH OM4 12G (1x12) SC-SC,50m Dca LSZH	50 m	2 mm	±5 %
O8341S60OM4	Trunk cable U-DQ(ZN)BH OM4 12G (1x12) SC-SC,60m Dca LSZH	60 m	2 mm	±5 %
O8341S70OM4	Trunk cable U-DQ(ZN)BH OM4 12G (1x12) SC-SC,70m Dca LSZH	70 m	2 mm	±5 %
O8341S80OM4	Trunk cable U-DQ(ZN)BH OM4 12G (1x12) SC-SC,80m Dca LSZH	80 m	2 mm	±5 %

This datasheet was created automatically on 19-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

DATASHEET

Trunk cable U-DQ(ZN)BH OM4 12G (1x12) SC-SC,50m Dca LSZH

O8341S90OM4	Trunk cable U-DQ(ZN)BH OM4 12G (1x12) SC-SC,90m Dca LSZH	90 m	2 mm	±5 %

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION