DATASHEET

U-DQ(ZN) BH G657A 4E9/125µm SC-SC, 1 Meter LSZH black CPR-B2CA



General data

Characteristics and advantages of Trunk cables:
- 2 up to 48 fibers per cable (CPR class B2ca)
- Pre-assembled, polished and factory-tested
- Both-sided assembled with stepped plug whips
- Ready to use, no need for expensive splice- and measuring equipment
- With Premium or Standard cable divider at customers choice
- Attenuation protocol for each assembled connector included in delivery
- All possible combinations of connectors like LC and SC
- Identification with cable markers
- Delivery depending on length and type: one way drum or cable ring

Technical properties

Cable Diameter	11.2 mm
Category	G657A1
Coding	1:1
Colour outer sheath	black
Connector connection 1	SC
Connector connection 2	SC
Crossed	No
Fibre type	G657A1 9/125
Flame retardant	nach IEC/EN 60332-3-24
Halogen free (according to EN 50267-2-3)	False
Material outer sheath	LSZH
Operating temperature	-5 – 60 °C
Storage Temperature	-40 – 80 °C
With rodent protection	True

Available variants

ArtNr.	Bezeichnung	Cable type connector connection 2	Length	Number of connectors connection 2	Number of fibres

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

DATASHEET

U-DQ(ZN) BH G657A 4E9/125µm SC-SC, 1 Meter LSZH black CPR-B2CA

O8421.1-B2	U-DQ(ZN) BH G657A 4E9/125µm SC-SC, 1 Meter LSZH black CPR-B2CA	Universal cable	1.0 m	4	4
O8431.1-B2	U-DQ(ZN) BH G657A 8E9/125µm SC-SC, 1 Meter LSZH black CPR-B2CA	Universal cable	1.0 m	8	8
O8441.1-B2	U-DQ(ZN) BH G657A 12E9/125µm SC - SC, 1 Meter LSZH black CPR-B2CA	Universal cable	1.0 m	12	12

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION