


DATASHEET

U-DQ(ZN)BH G657A 9/125µm ST/SC 4E 1,0m



General data

Characteristics and advantages of Trunk cables:

- 2 up to 48 fibers per cable (other Trunks available on request)
- Pre-assembled, polished and factory-tested
- Both-sided assembled with stepped plug whips
- Ready to use, no need for expensive splice- and measuring equipment
- With Premium or Standard cable divider at customers choice
- Attenuation protocol for each assembled connector included in delivery
- All possible combinations of connectors like LC, E2000®, SC and ST available
- Identification with cable markers
- Delivery depending on length and type: one way drum or cable ring

Technical properties

Category	G657A1
Coding	1:1
Colour outer sheath	black
Connector connection 1	ST
Connector connection 2	SC
Crossed	No
Fibre type	G657A1 9/125
Flame retardant	acc. to EN 50265-2-1
Halogen free (according to EN 50267-2-3)	True
Material outer sheath	LSZH
Operating temperature	-20 – 60 °C
Storage Temperature	-40 – 80 °C

This datasheet was created automatically on 07-10-2026 . Technical changes reserved.



DATASHEET

U-DQ(ZN)BH G657A 9/125µm ST/SC 4E 1,0m

With rodent protection

True

Available variants

ArtNr.	Bezeichnung	Length	Number of connectors connection 1	Number of connectors connection 2	Number of fibres
O8161.1	U-DQ(ZN)BH G657A 9/125µm ST/SC 24E 1,0m	1.0 m	24	24	24
O8451.1	U-DQ(ZN)BH G657A 9/125µm ST/SC 8E 1,0m	1.0 m	8	8	8
O8801.1	U-DQ(ZN)BH G657A 9/125µm ST/SC 4E 1,0m	1.0 m	4	4	4
O8811.1	U-DQ(ZN)BH G657A 9/125µm ST/SC 12E 1,0m	1.0 m	12	12	12
O8845.1	U-DQ(ZN)BH G657A 9/125µm ST/SC 48E 1,0m	1.0 m	48	48	48

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 07-10-2026 . Technical changes reserved.

