
DATASHEET

A-DQ(ZN) B2Y G657A 9/125µm ST/ST 24E 1,0m



General data

Outdoor Suitable for direct burial, duct or shaft installation
Primary cabling (Campus), Backbone
PE jacket black , non-metallic, longitudinal water tight
UV resistant, rodent resistant
Central/Loose tubes, 250µm coating. The cable diameter can vary.

Characteristics and advantages of Trunk cables:
• 2 up to 48 fibers per cable (other Trunks available on request)
• Pre-assembled, polished and factory-tested
• Both-sided assembled with stepped plug whips
• Ready to use, no need for expensive splice- and measuring equipment
• With Premium or Standard cable divider at customers choice
• Attenuation protocol for each assembled connector included in delivery
• All possible combinations of connectors like LC, E2000®, SC and ST available
• Identification with cable markers
• Delivery depending on length and type: one way drum or cable ring

Technical properties

Category	G657A1
Coding	1:1
Colour outer sheath	black
Connector connection 1	ST
Connector connection 2	ST
Crossed	No
Fibre type	G657A1 9/125
Flame retardant	No
Halogen free (according to EN 50267-2-3)	False
Material outer sheath	PE
Operating temperature	-25 – 60 °C
Storage Temperature	-25 - 70 °C
With rodent protection	True

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

DATASHEET

A-DQ(ZN) B2Y G657A 9/125µm ST/ST 24E 1,0m

Available variants

ArtNr.	Bezeichnung	Length	Number of connectors connection 1	Number of connectors connection 2	Number of fibres
O8121.1ADQ	A-DQ(ZN) B2Y G657A 9/125µm ST/ST 4E 1,0m	1.0 m	4	4	4
O8131.1ADQ	A-DQ(ZN) B2Y G657A 9/125µm ST/ST 8E 1,0m	1.0 m	8	8	8
O8141.1ADQ	A-DQ(ZN) B2Y G657A 9/125µm ST/ST 12E 1,0m	1.0 m	12	12	12
O8821.1ADQ	A-DQ(ZN) B2Y G657A 9/125µm ST/ST 24E 1,0m	1.0 m	24	24	24

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION