


# DATASHEET

## Trunkkabel U-DQ(ZN)BH OS2 24E LC-LC 120m Dca LSZH G657A1



AI 1000110

### General data

#### EFB-Elektronik sets standards in high quality

For many years, EFB-Elektronik has been offering individual fiber optic assemblies from its own production for insertion into cable ducts and shafts. Now there is also a standard line, which is kept in stock. These are pre-assembled trunk cables with LC connectors in the OS2, OM3 and OM4 categories. The stocked lengths can be found in the overview below.

#### Advantages:

**Fast delivery:** standard lengths up to 200 m in standard quantities available from stock

**Reduction of installation costs:** No splicing and assembly equipment required

**Reduced installation time:** cable ready for direct installation

This datasheet was created automatically on 11-09-2026 . Technical changes reserved.



# DATASHEET

## Trunkkabel U-DQ(ZN)BH OS2 24E LC-LC 120m Dca LSZH G657A1

**Traceable quality:** cable with serial number and measurement protocol

### Performance features:

4, 8 or 12 fibers per cable

Fibre class OS2, OM3 or OM4

Factory production, polishing and function test

Double-sided assembled stepped cable whips (longest length 1 m)

Identification of the remote individual cables with cable markers (numbers)

Serial number on the cable

Attenuation protocol for each individual fiber is provided

Delivery on both sides with fabric hose as drawing-in tube

Delivery up to 40 m in polybag, from 50 m on disposable drum

Raw cable: CPR-Class Dca

Length of the draw-in tube of 130cm, diameter: 4 fiber approx. 10mm, 8 fiber approx. 15mm, 12 fiber approx. 20mm

### Technical properties

|                               |                                                                      |
|-------------------------------|----------------------------------------------------------------------|
| Anti-kink sleeve              | put-on                                                               |
| Bend optimized fiber          | yes                                                                  |
| CPR class                     | Dca                                                                  |
| Cable structure               | Multifiber                                                           |
| Cable type                    | U-DQ (ZN) BH                                                         |
| Cable Ø                       | 6 mm                                                                 |
| Category                      | OS2 G657A1                                                           |
| Colour outer sheath           | black                                                                |
| Dimension Cable divider       | 11.5 x 372 mm                                                        |
| Fibre type                    | Single mode 9/125                                                    |
| Flame retardant               | Yes                                                                  |
| Halogen free                  | True                                                                 |
| Insertion loss 1310nm         | < 0.25 dB                                                            |
| Material outer sheath         | LSZH                                                                 |
| Max. Tension (long term)      | 200 N                                                                |
| Min. Bending radius (Dynamic) | 30xOD mm                                                             |
| Min. Bending radius (Static)  | 15xOD mm                                                             |
| Number of fibres              | 24                                                                   |
| Operating Temperature         | -20 - 70 °C                                                          |
| Packaging                     | < 50m polybag & >50m spool                                           |
| Return loss 1310nm            | >=50                                                                 |
| Scope of delivery             | Cable, measurement protocol, GPSR instruction leaflet, insertion aid |

This datasheet was created automatically on 11-09-2026 . Technical changes reserved.



# DATASHEET

## Trunkkabel U-DQ(ZN)BH OS2 24E LC-LC 120m Dca LSZH G657A1

|                                |             |
|--------------------------------|-------------|
| Storage Temperature            | -20 – 70 °C |
| Type of connector connection 1 | LC          |
| Type of connector connection 2 | LC          |

### Available variants

| ArtNr.       | Bezeichnung                                              | Length |
|--------------|----------------------------------------------------------|--------|
| O8832S100OS2 | Trunkkabel U-DQ(ZN)BH OS2 24E LC-LC 100m Dca LSZH G657A1 | 100 m  |
| O8832S100S2  | Trunkkabel U-DQ(ZN)BH OS2 24E LC-LC 10m Dca LSZH G657A1  | 10 m   |
| O8832S120OS2 | Trunkkabel U-DQ(ZN)BH OS2 24E LC-LC 120m Dca LSZH G657A1 | 120 m  |
| O8832S150OS2 | Trunkkabel U-DQ(ZN)BH OS2 24E LC-LC 150m Dca LSZH G657A1 | 150 m  |
| O8832S200OS2 | Trunkkabel U-DQ(ZN)BH OS2 24E LC-LC 200m Dca LSZH G657A1 | 200 m  |
| O8832S200S2  | Trunkkabel U-DQ(ZN)BH OS2 24E LC-LC 20m Dca LSZH G657A1  | 20 m   |
| O8832S300S2  | Trunkkabel U-DQ(ZN)BH OS2 24E LC-LC 30m Dca LSZH G657A1  | 30 m   |
| O8832S400S2  | Trunkkabel U-DQ(ZN)BH OS2 24E LC-LC 40m Dca LSZH G657A1  | 40 m   |
| O8832S500S2  | Trunkkabel U-DQ(ZN)BH OS2 24E LC-LC 50m Dca LSZH G657A1  | 50 m   |
| O8832S50S2   | Trunkkabel U-DQ(ZN)BH OS2 24E LC-LC 5m Dca LSZH G657A1   | 5 m    |
| O8832S700S2  | Trunkkabel U-DQ(ZN)BH OS2 24E LC-LC 70m Dca LSZH G657A1  | 70 m   |

### Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 11-09-2026 . Technical changes reserved.

