
DATASHEET

Network Cabinet OFFICE 15U, 600x600 mm, RAL9005













General data

The 19" OFFICE network cabinet from EFB-Elektronik in 600 x 600 mm and RAL 9005 is designed for the structured installation of network and IT components in the office and technical sector. The self-supporting, completely pre-assembled frame offers 15 U and combines compact dimensions with practical equipment for active and passive components.

• All-glass door made of certified safety glass with 4 mm glass thickness – Allows visual inspection of the equipment and combines transparency with robust front design.
• Passively ventilated 19" format with cable entries in the roof, floor and rear wall – Supports clean routing without active cooling.
• Self-supporting, fully pre-assembled frame – Reduces assembly effort and creates a stable base for removal.

In terms of technical design, the cabinet is designed for installations with limited space requirements and orderly wiring effort. The passive ventilation and the break-out cable entries in the roof, floor and rear wall support clean

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

Network Cabinet OFFICE 15U, 600x600 mm, RAL9005

cable feeding. Front and rear mounting levels facilitate assembly, while the replaceable door hinge simplifies adaptation to the structural installation situation.

Technical details
- Number of doors: 1
- Degree of protection: IP20 according to EN 60529
- Type of ventilation: passive
- With earthing: Yes
- With roof panel: Yes
- With front door: Yes
- With side panels: Yes
- Mounting level: front and rear
- Front door design: one-piece full glass door (certified safety glass, glass thickness 4 mm)
- Front door locking: 1-point quarter-turn latch
- Scope of delivery: 1x cabinet, 1 x brush strip, 4 x levelling feet M8, 2 x keys
- Packaging: Delivered in transport packaging on a single-use pallet

Technical properties	
Active air conditioning	False
Cabinet Series	Office
Cable entry rear door	2 x pre-cut, breakable openings, each approx. 245 x 35 mm
Cable entry roof/floor	2 pre-cut, breakable openings (1 x roof, 1 x base), each approx. 245 x 35 mm
Category	19" network cabinet according to DIN41494
Degree of protection	IP20 according to EN60529
Demountable	False
Door hinge reversible front door	True
Frame	self-supporting, completely pre-assembled
Material	Steel
Model	With permanent frame
Modular spacing	482,6 mm (19 inch)
Mounting level	Front and rear
PHC replaceable front door	False,
PHC replaceable rear door	False
Packaging	Delivery in transport packaging on a disposable pallet
Scope of delivery	1x cabinet, 1 x brush strip, 4 x leveling feet M8, 2 x keys
Stackable	False
Surface finishing	Powder coating
Toolless depth adjustment	False
Type of back door	Rear wall

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

DATASHEET

Network Cabinet OFFICE 15U, 600x600 mm, RAL9005

Type of front door	Full glass door 1-part (certified safety glass, glass thickness 4 mm)
Type of profile rail	L-shaped
Type of ventilation	Passive
With backside door	False
With earthing	True
With front door	True
With roof plate	True
With sidewall	True
With socket	False

Available variants

ArtNr.	Bezeichnung	Colour	Depth	Front door locking system	Material front door	Material rear door	Max. load capacity	Number of height units	Width	With vertical cable management	Height	RAL-number	Number of doors
OFF-1266TS.V1RW	Network Cabinet OFFICE 12U, 600x600 mm, RAL9005	black	600 mm	1-point latch locking mechanism	Glass	Steel	30 kg	12 U	600 mm	False	604 mm	9005	1
OFF-1566TS.V1RW	Network Cabinet OFFICE 15U, 600x600 mm, RAL9005	black	600 mm	1-point latch locking mechanism	Glass	Steel	38 kg	15 U	600 mm	False	737 mm	9005	1
OFF-1866TS.V1RW	Network Cabinet OFFICE 18U, 600x600 mm, RAL9005	black	600 mm	1-point latch locking mechanism	Glass	Steel	45 kg	18 U	600 mm	False	871 mm	9005	1

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION