DATASHEET

Network Cabinet OFFICE 15U, 600x800 mm, RAL7035







General data

The 19" OFFICE network cabinet from EFB-Elektronik in 600 x 800 mm and RAL 7035 is designed for structured installation in the network and IT environment. It combines a compact design with practical equipment and is suitable for installations with moderate space requirements and manageable cabling effort.

• Full glass door made of certified safety glass – Enables visual inspection of the installed components and supports a clear overview during operation.
• Passive ventilation with cable entries in the roof, floor and rear wall – Ensures clean ducting without active cooling.
• Self-supporting, fully pre-assembled frame with interchangeable front door hinge – simplifies assembly and makes it easier to adapt to the installation situation.

With 15 U, a grid dimension of 482.6 mm and a load capacity of 38 kg, the cabinet is designed for typical office and network installations. The powder-coated steel housing in grey has a mounting level at the front and rear as well as earthing and protection class IP20 in accordance with EN 60529. The front door is designed as a one-piece glass door with 4 mm safety glass. The equipment is supplemented by pre-punched, break-out cable entries in the roof, floor and rear wall as well as by delivery as a transportable, pre-assembled unit.

Technical details
• Number of doors: 1
• Degree of protection: IP20 according to EN 60529
• Type of ventilation: passive

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

DATASHEET

Network Cabinet OFFICE 15U, 600x800 mm, RAL7035

- With earthing: Yes
- With roof panel: Yes
- With front door: Yes
- With side panels: Yes
- Mounting level: front and rear
- Front door design: one-piece full glass door (certified safety glass, glass thickness 4 mm)
- Front door locking: 1-point pre-latch access
- Scope of delivery: 1x cabinet, 1 x brush strip, 4 x levelling feet M8, 2 x keys
- Packaging: Delivered in transport packaging on a single-use pallet

Technical properties	
Active air conditioning	False
Cabinet Series	Office
Cable entry rear door	2 x pre-cut, breakable openings, each approx. 245 x 35 mm
Cable entry roof/floor	2 pre-cut, breakable openings (1 x roof, 1 x base), each approx. 245 x 35 mm
Category	19" network cabinet according to DIN41494
Degree of protection	IP20 according to EN60529
Demountable	False
Door hinge reversible front door	True
Frame	self-supporting, completely pre-assembled
Material	Steel
Model	With permanent frame
Modular spacing	482,6 mm (19 inch)
Mounting level	Front and rear
PHC replaceable front door	False,
PHC replaceable rear door	False
Packaging	Delivery in transport packaging on a disposable pallet
Scope of delivery	1x cabinet, 1 x brush strip, 4 x leveling feet M8, 2 x keys
Stackable	False
Surface finishing	Powder coating
Toolless depth adjustment	False
Type of back door	Rear wall
Type of front door	Full glass door 1-part (certified safety glass, glass thickness 4 mm)
Type of profile rail	L-shaped
Type of ventilation	Passive
With backside door	False
With earthing	True

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

DATASHEET

Network Cabinet OFFICE 15U, 600x800 mm, RAL7035

With front door	True
With roof plate	True
With sidewall	True
With socket	False

Available variants

ArtNr.	Bezeichnung	Colour	Depth	Front door locking system	Material front door	Material rear door	Max. load capacity	Number of height units	Width	With vertical cable management	Height	RAL-number	Number of doors
OFF-1568GR.V1RW	Network Cabinet OFFICE 15U, 600x800 mm, RAL7035	grey	800 mm	1-point latch locking mechanism	Glass	Steel	38 kg	15 U	600 mm	False	737 mm	7035	1
OFF-1868GR.V1RW	Network Cabinet OFFICE 18U, 600x800 mm, RAL7035	grey	800 mm	1-point latch locking mechanism	Glass	Steel	45 kg	18 U	600 mm	False	871 mm	7035	1

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION