



DATASHEET

19"Network Cabinet PEL 24HE 600x600 RAL7035 front glass 1-pc. rear steel 1-pc



General data

The 19-inch network cabinet of the PEL series from EFB-Elektronik in RAL 7035 is designed for the structured installation of network and IT components. With 24 U, a completely pre-assembled frame and a maximum load capacity of 800 kg, it combines mechanical stability with practical equipment for demanding installations.

- 24U in 19-inch format and 800 kg maximum load capacity – Provides high reserves for active and passive components and remains stable even with dense loads.
- Front door made of one-piece safety glass and rear steel door – Enables visual inspection at the front and at the same time robustly protects the installed technology from the outside.
- Passive ventilation, baying-compatible design and cable entries in the roof and floor – Supports flexible installations with clean routing without active cooling.

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

DATASHEET

19"Network Cabinet PEL 24HE 600x600 RAL7035 front glass 1-pc. rear steel 1-pc

The design is designed for thermally non-critical operation and efficient construction in the control cabinet and network omer field. The screwed, completely pre-assembled frame simplifies assembly. The doors can be hinged on both sides and open up to 180 ° each, which simplifies maintenance work and removal in a row arrangement. This is complemented by the bolted, resealable openings in the roof and floor as well as the mounting levels at the front and rear.

Technical details

- Number of doors: 2
- Degree of protection: IP20 according to EN 60529
- Type of ventilation: passive
- With earthing: Yes
- With roof panel: Yes
- With front door: Yes
- With side panels: Yes
- With rear door: Yes
- Mounting level: front and rear
- Front door design: one-piece glass door, certified safety glass, glass thickness 4 mm
- Front door opening angle: 180 °
- Rear door opening angle: 180°
- Front door locking: 1-point quarter-turn latch with swing handle
- Rear door locking: 1-point quarter-turn latch
- Reversible front door hinging: Yes
- Reversible rear door hinging: Yes
- Scope of delivery: 1x cabinet, 4 x levelling feet, cage nut set 20 pieces, key
- Packaging: Delivered in transport packaging on a single-use pallet
- Rear door design: one-piece steel door
- Width: 600 mm
- Height: 1200 mm
- Depth: 600 mm
- Number of rack units (U): 24 U
- Baying compatible: Yes
- Max. load capacity: 800 kg
- Design: with fixed frame
- Finish of the surface: powder-coated
- Colour: grey
- RAL number: 7035

Technical properties

Active air conditioning	False
Cabinet Series	PEL
Cable entry roof/floor	Roof and base each 2 screwed openings (front, rear), each 386 x 69 mm (re-sealable with pre-mounted blanking plates)

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

DATASHEET

19"Network Cabinet PEL 24HE 600x600 RAL7035 front glass 1-pc. rear steel 1-pc

Category	19" network cabinet according to DIN41494
Degree of protection	IP20 according to EN60529
Demountable	True
Door hinge reversible front door	True
Door hinge reversible rear door	True
Door opening angle front door	180 °
Door opening angle rear door	180 °
Frame	screwed together, completely pre-assembled
Material	Steel
Model	With permanent frame
Modular spacing	482,6 mm (19 inch)
Mounting level	Front and rear
PHC replaceable front door	False,
PHC replaceable rear door	False
Packaging	Delivery in transport packaging on a disposable pallet
Scope of delivery	1x cabinet, 4 x leveling feet, cage nut set (20 pieces), key
Stackable	True
Surface finishing	Powder coating
Type of back door	Steel door 1-part
Type of front door	Glass door 1-part (certified safety glass, glass thickness 4 mm)
Type of profile rail	Crank
Type of ventilation	Passive
With backside door	True
With earthing	True
With front door	True
With roof plate	True
With sidewall	True
With socket	False

Available variants

ArtNr.	Bezeichnung	Colour	Depth	Front door locking system	Material front door	Material rear door	Max. load capacity	Number of height units	Rear door locking system	With vertical cable management	Height	RAL-number	Number of doors
--------	-------------	--------	-------	---------------------------	---------------------	--------------------	--------------------	------------------------	--------------------------	--------------------------------	--------	------------	-----------------

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.



DATASHEET

19"Network Cabinet PEL 24HE 600x600 RAL7035 front glass 1-pc. rear steel 1-pc

PEL-2466GR.G1SV	19"Network Cabinet PEL 24HE 600x600 RAL7035 front glass 1-pc. rear steel 1-pc	grey	600 mm	1-point latch locking mechanism with swivel lever	Glass	Steel	800 kg	24 U	1-point latch locking mechanism	600 mm	False	1200 mm	7035	2
PEL-4266GR.G1SV	19"Network Cabinet PEL 42HE 600x600 RAL7035 front glass 1-pc. rear steel 1-pc	grey	600 mm	1-point latch locking mechanism with swivel lever	Glass	Steel	800 kg	42 HE	1-point latch locking mechanism	600 mm	False	2000 mm	7035	2
PEL-4280GR.G1SV	19"Network Cabinet PEL 42HE 800x1000 RAL7035 front glass 1-pc. rear steel 1-pc	grey	1000 mm	1-point latch locking mechanism with swivel lever	Glass	Steel	800 kg	42 HE	1-point latch locking mechanism	800 mm	False	2000 mm	7035	2
PEL-4288GR.G1SV	19"Network Cabinet PEL 42HE 800x800 RAL7035 front glass 1-pc. rear steel 1-pc	grey	800 mm	1-point latch locking mechanism with swivel lever	Glass	Steel	800 kg	42 HE	1-point latch locking mechanism	800 mm	False	2000 mm	7035	2

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

