


DATASHEET

19" Network Cabinet PEL 42HE 800x1000 RAL7035 front glass 1-pc. rear steel 1-pc



General data

The 19" PEL network cabinet in 800 x 1000 mm and RAL 7035 is designed for the structured installation of active and passive components in the network and IT environment. The completely pre-assembled, bolted construction with fixed frame combines mechanical stability with practical equipment for daily operation.

- 42U in 19-inch pitch and 1000mm deep – Provide generous installation space for large-scale network installations and high-performance components.
- One-piece glass door at the front and one-piece steel door at the rear – Allow visual inspection with robust protection and facilitate access to the installed technology.
- Passive ventilation, IP20 and baying-compatible design – Support low-maintenance indoor operation and create room for later expansion.

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

DATASHEET

19"Network Cabinet PEL 42HE 800x1000 RAL7035 front glass 1-pc. rear steel 1-pc

The cabinet is designed for installations with a high space requirement and structured cabling effort. The mounting levels at the front and rear make it easy to assemble, while the cable entries in the roof and floor, each with two screwed openings, enable clean cable routing. The resealable blank plates support flexible use without unnecessary openings in the housing. With a load capacity of 800 kg, earthing and IP20 protection, the system is suitable for reliable use in closed IT environments.

Technical details

- Number of doors: 2
- Degree of protection: IP20 according to EN 60529
- Type of ventilation: passive
- With earthing: Yes
- With roof panel: Yes
- With front door: Yes
- With side panels: Yes
- With rear door: Yes
- Mounting level: front and rear
- Front door design: one-piece glass door (certified safety glass, glass thickness 4 mm)
- Front door opening angle: 180 °
- Rear door opening angle: 180°
- Front door locking: 1-point quarter-turn latch with swing handle
- Rear door locking: 1-point quarter-turn latch
- Scope of delivery: 1x cabinet, 4 x levelling feet, cage nut set 40 pieces, wrench
- Packaging: Delivered in transport packaging on a single-use pallet

Technical properties

Active air conditioning	False
Cabinet Series	PEL
Cable entry roof/floor	Roof and base each 2 screwed openings (front, rear), each 386 x 69 mm (re-sealable with pre-mounted blanking plates)
Category	19" network cabinet according to DIN41494
Degree of protection	IP20 according to EN60529
Demountable	True
Door hinge reversible front door	True
Door hinge reversible rear door	True
Door opening angle front door	180 °
Door opening angle rear door	180 °
Frame	screwed together, completely pre-assembled
Material	Steel
Model	With permanent frame
Modular spacing	482,6 mm (19 inch)

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.



DATASHEET

19"Network Cabinet PEL 42HE 800x1000 RAL7035 front glass 1-pc. rear steel 1-pc

Mounting level	Front and rear
PHC replaceable front door	False,
PHC replaceable rear door	False
Packaging	Delivery in transport packaging on a disposable pallet
Scope of delivery	1x cabinet, 4 x leveling feet, cage nut set (20 pieces), key
Stackable	True
Surface finishing	Powder coating
Type of back door	Steel door 1-part
Type of front door	Glass door 1-part (certified safety glass, glass thickness 4 mm)
Type of profile rail	Crank
Type of ventilation	Passive
With backside door	True
With earthing	True
With front door	True
With roof plate	True
With sidewall	True
With socket	False

Available variants

ArtNr.	Bezeichnung	Colour	Depth	Front door locking system	Material front door	Material rear door	Max. load capacity	Number of height units	Rear door locking system	Width	With vertical cable management	Height	RAL-number	Number of doors
PEL-2466GR.G1SV	19"Network Cabinet PEL 24HE 600x600 RAL7035 front glass 1-pc. rear steel 1-pc	grey	600 mm	1-point latch locking mechanism with swivel lever	Glass	Steel	800 kg	24 U	1-point latch locking mechanism	600 mm	False	1200 mm	7035	2
PEL-4266GR.G1SV	19"Network Cabinet PEL 42HE 600x600 RAL7035 front glass 1-pc. rear steel 1-pc	grey	600 mm	1-point latch locking mechanism with swivel lever	Glass	Steel	800 kg	42 HE	1-point latch locking mechanism	600 mm	False	2000 mm	7035	2
PEL-4280GR.G1SV	19"Network Cabinet PEL 42HE 800x1000 RAL7035 front glass 1-pc. rear steel 1-pc	grey	1000 mm	1-point latch locking mechanism with swivel lever	Glass	Steel	800 kg	42 HE	1-point latch locking mechanism	800 mm	False	2000 mm	7035	2

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.



DATASHEET

19"Network Cabinet PEL 42HE 800x1000 RAL7035 front glass 1-pc. rear steel 1-pc

PEL-4288GR.G1SV	19"Network Cabinet PEL 42HE 800x800 RAL7035 front glass 1-pc. rear steel 1-pc	grey	800 mm	1-point latch locking mechanism with swivel lever	Glass	Steel	800 kg	42 HE	1-point latch locking mechanism	800 mm	False	2000 mm	7035	2
-----------------	---	------	--------	---	-------	-------	--------	-------	---------------------------------	--------	-------	---------	------	---

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

