

# DATASHEET

## 24V DC Industrial Power Supply 60W, DIN rail mounting



### General data

The **POW-2421** is a high-quality, robust, universal industrial power supply for DIN rail mounting that meets all major safety and EMC standards. It is also UL-approved. It can operate at full load over an ambient temperature range of -30 to 70 degrees Celsius without additional cooling, ensuring operational reliability even in harsh industrial environments.

### Technical properties

|                                |         |
|--------------------------------|---------|
| 1st secondary output voltage   | 24 V    |
| Depth                          | 52.5 mm |
| Height                         | 54.5 mm |
| Rail mounting possible         | True    |
| Voltage type of supply voltage | DC      |
| Wall mounting possible         | False   |
| Width                          | 90 mm   |

This datasheet was created automatically on 20-09-2026 . Technical changes reserved.



# DATASHEET

## 24V DC Industrial Power Supply 60W, DIN rail mounting

### Available variants

| ArtNr.   | Bezeichnung                                           | Max. output current | Power output |
|----------|-------------------------------------------------------|---------------------|--------------|
| POW-2421 | 24V DC Industrial Power Supply 60W, DIN rail mounting | 2.5 A               | 60 W         |

### Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 20-09-2026 . Technical changes reserved.

