DATASHEET

24V DC Industrial Power Supply 60W, DIN rail mounting









General data

The **POW-2421** is a high-quality, robust, universal industrial power supply for DIN rail mounting that meets all major safety and EMC standards. It is also UL-approved. It can operate at full load over an ambient temperature range of -30 to 70 degrees Celsius without additional cooling, ensuring operational reliability even in harsh industrial environments.

Technical properties

1st secondary output voltage	24 V
Depth	52.5 mm
Height	54.5 mm
Rail mounting possible	True
Voltage type of supply voltage	DC
Wall mounting possible	False
Width	90 mm

This datasheet was created automatically on 04-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

DATASHEET

24V DC Industrial Power Supply 60W, DIN rail mounting

Available variants

ArtNr.	Bezeichnung	Max. output current 1	Power output
POW-2421	24V DC Industrial Power Supply 60W, DIN rail mounting	2.5 A	60 W

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION